

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LDR212BC-NB

	Mirina	Dimanaian -
Item Image	Wiring	Dimensions
		Hamilton Linea DUO CFX
		R212 2 Way Rocker
	Alternation 2 very sweltzbrig  Lore In Lore Out  Lore Out	2 way Rocker
		86.0
Primary Range	Linea-Duo CFX	
Insert Type	1 gang 20AX 2 Way Rocker	
Plate Finish	Linea-Duo CFX Bright Chrome Frame/Piano Black	
Insert Colour	Bright Chrome/Black	
EAN13 Barcode	5017504040239	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	Single	
Current Rating	20AX	
Voltage	220/250V AC	
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	2 x 2.5mm2	
Terminal Capacity 4	2 x 4mm2 Multi-strand	
Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval Patents and Trademarks	BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	Linea-Duo CFX is a UK Registered Design Certificate No: R2  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.	1 = 3021173 SS2 = 3021174  It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:19 A E&C

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio