

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

Linea-Duo CFX Satin Nickel Frame/Satin Steel Front 1 gang 20AX 2 Way Rocker Satin Steel/Black  Item Image  Wiring  Dimensions  Hemilton  Ulter A 000 577  1 gang 20AX 2 Way Rocker  Insert Type  Satin Steel/Black  EAN13 Barcode  5017504226387  Dimensions (Nominal)  Finight Fold Centres  Roc Fixing + 86.0mm Width + 86.0mm Depth + 4.0mm  Fixing Hold Centres  Roc Fixing + 60.0mm Grid Fixing - GFX Clips  Minimum Wall Box Depth  Shrm  Switched Pobs  Single  Current Rating  20AX  Voltage  220250V AC  Maximum Load  Alian Frequency  50Hz  1 gang 20AX 2 Way Rocker  1 gang 20AX 2 Way Rocker  Insert Type  Ins	LDR212SN-SSB			
High	Linea-Duo CFX Satin Nickel Frame/Satin Steel Front 1 gang 20AX 2 Way Rocker Satin Steel/Black			
Primary Range Lines-Duo CFX Insert Type 1 gang 20AX 2 Way Rocker Insert Type 1 gang 20AX 2 Way Rocker Insert Type 3 gang 20AX 2 Way Rocker Insert Clour Satin Nickel Frame/Satin Steel Insert Colour Satin Steel/Black EAN13 Barcode 5017504226367 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centree Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 3 x 2.5mm2 Earth Terminal Capacity 4 3 x 2.5mm2 Earth Terminal Capacity 4 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	Item Image	Wiring	Dimensions	
Primary Range         Linea-Duo CFX           Insert Type         1 gang 20AX 2 Way Rocker           Plate Finish         Linea-Duo CFX Satin Nickel Frame/Satin Steel           Insert Colour         Satin Steel/Black           EAN13 Barcode         5017504226367           Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Single           Current Rating         20AX           Voltage         220/250V AC           Maximum Load         20 Amp Inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         2 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand			R212	
Insert Type		Abternative 2 very sentrange		
Plate Finish         Linea-Duo CFX Satin Nickel Frame/Satin Steel           Insert Colour         Satin Steel/Black           EAN13 Barcode         5017504226367           Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Single           Current Rating         20AX           Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         2 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand	nary Range	Linea-Duo CFX		
Insert Colour   Satin Steel/Black	ert Type	1 gang 20AX 2 Way Rocker		
EAN13 Barcode         5017504226367           Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Single           Current Rating         20AX           Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         2 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         6 x 1mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand	te Finish	Linea-Duo CFX Satin Nickel Frame/Satin Steel		
Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Single           Current Rating         20AX           Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         2 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand	ert Colour	Satin Steel/Black		
Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Switched Poles  Single  Current Rating  20AX  Voltage  220/250V AC  Maximum Load  Mains Frequency  Mains Frequency  IP Rating  Pexto  Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 1  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4	N13 Barcode	5017504226367		
Minimum Wall Box Depth Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	nensions (Nominal)			
Switched Poles         Single           Current Rating         20AX           Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         2 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand	ng Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating         20AX           Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         2 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand	imum Wall Box Depth	35mm		
Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         2 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand	tched Poles	Single		
Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         2 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand	rent Rating	20AX		
Mains Frequency       50Hz         IP Rating       IP2XD         Contact Gap Minimum       3mm         Terminal Capacity 1       5 x 1mm2         Terminal Capacity 2       4 x 1.5mm2         Terminal Capacity 3       2 x 2.5mm2         Terminal Capacity 4       2 x 4mm2 Multi-strand         Terminal Capacity 5       1 x 6mm2         Earth Terminal Capacity 1       6 x 1mm2         Earth Terminal Capacity 2       5 x 1.5mm2         Earth Terminal Capacity 3       3 x 2.5mm2         Earth Terminal Capacity 4       2 x 4mm2 Multi-strand	tage			
IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5 x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 2 x 2.5mm2  Terminal Capacity 4 2 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 5 x 1.5mm2  Earth Terminal Capacity 4 5 x 1.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	ximum Load	20 Amp inductive		
Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand	ns Frequency	50Hz		
Terminal Capacity 1 5 x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 2 x 2.5mm2  Terminal Capacity 4 2 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	Rating	IP2XD		
Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 2 x 2.5mm2  Terminal Capacity 4 2 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	ntact Gap Minimum	3mm		
Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand	minal Capacity 1	5 x 1mm2		
Terminal Capacity 4 2 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	minal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand	minal Capacity 3			
Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	minal Capacity 4			
Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	minal Capacity 5			
Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	th Terminal Capacity 1			
Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	th Terminal Capacity 2			
	th Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 5   1 x 6mm2	th Terminal Capacity 4	2 x 4mm2 Multi-strand		
	th Terminal Capacity 5	1 x 6mm2		
Product Class 1 Must be earthed	duct Class 1			
Ambient Operating Temperature -5° to +40°C	bient Operating Temperature			
Recommended Location Internal Use Only	commended Location			
Maximum Installation Altitude 2000m	ximum Installation Altitude			
Standard/Approval BS EN 60669-1	ndard/Approval			
Linea is a Registered Trade Mark No 2398665  Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	ents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding.  guarantee an exact colour match and shadings of of certain finishes.	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 15 October 2018 08:19 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio