

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

	LDR22BC-BKB			
Primary Range Unea-Duo CFX Inventory 2 2 gang 10M 2 Way Rucker Invent Typu 2 2 gang 10M 2 Way Rucker Plans Finish Unan Duo CFX Rejnit Chorana Shack Nickel Inventory 3 (17504692214) Inventory 3 (17504692214) Inventory 4 (17504692214) Inventory 4 (17504692214) Inventory 5 (175046924) I	Linea-Duo CFX Bright Chrome Frame/Black Nickel Front 2 gang 10AX 2 Way Rocker Bright Chrome/Black			
Primary Range Linea Duo CFX Insert Type 2 gang 10AX 2 Way Rocker Please Finah Linea-Duo CFX Right Chome Farmwellack Nickel Insert Coor Bright Chome Street Chome Insert Chome Street Cho	Item Image	Wiring	Dimensions	
Primary Range Linea-Duo CFX InneaT Type 2 gang 10AX 2 Way Rooker Plate Finish Linea-Duo CFX Bright Chrome Frame/Black Nickel Inneat Colour Bright Chrome/Black EAN13 Barcode 501750492221 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Finight Ede Centres Box Fising = 69.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 20mm Switched Poles Single Current Rating 10AX Voltage Single 220250V AC Maximum Load 10 Amp Inductive Mains Fraquency 504-2 IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x tmm2 Terminal Capacity 1 5 x tmm2 Terminal Capacity 2 1 x 6.mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 1 5 x tmm2 Terminal Capacity 3 1 x 6.mm2 Terminal Capacity 3 5 x 5.mm2 Terminal Capacity 4 5 x tmm2 Terminal Capacity 5 1 x 6.mm2 Terminal Capacity 5 1 x 6.mm2 Terminal Capacity 6 1 x 6.mm2 Terminal Capacity 7 5 x 6.mm2 Terminal Capacity 8 1 x 6.mm2 Terminal Capacity 9 5		The state of the s	R22 2 Way Rocker	
Neset Type		Alternative 2 vary switching Only In Long Cut Intermediate switching	88.0	
Pate Finish	Primary Range	Linea-Duo CFX		
Reaft Colour	Insert Type	2 gang 10AX 2 Way Rocker		
EAN13 Barcode \$017504092221 Dimensions (Nominal) Single: Height = 86.mm Width = 86.mm Depth = 4.0mm Fishing Hole Centres Box Fising = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Minins Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x fmm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 4 x 1.5mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 4 x 1.5mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 9	Plate Finish	Linea-Duo CFX Bright Chrome Frame/Black Nickel		
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing pe 60.3mm Grid Fixing = 60.3mm Grid Fixing = 60.3mm Depth = 4.0mm Switched Poles Single Switched Poles Switched Pole	Insert Colour	Bright Chrome/Black		
Riving Hole Centres	EAN13 Barcode	5017504092221		
Mninum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5** to 440***C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 80669-1 <td>Dimensions (Nominal)</td> <td colspan="2"></td>	Dimensions (Nominal)			
Switched Poles Single Current Rating 10AX Voltage 220′250′V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000	Fixing Hole Centres			
Current Rating 10AX Voltage 220/250 V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ms be earthed Ambient Operating Temperature -5" to +40"C Recommended Location Internal Use Only Maximum Installation Altitude 200m Standard/Approval BS EN 60669-1 European standard and the product information is correct at the	Minimum Wall Box Depth			
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 European standard and the produ	Switched Poles			
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-istrand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-istrand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383756 CFX is a	Current Rating			
Mains Frequency 50Hz IP Rating IP2DD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 4mm2 Multi-strand Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 4 x 1.5mm2 Earth Terminal Capacity 5 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5" to +40"C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea Registered Trade Mark No 2398667 CEX is a Registered Trade Mark No 2398667 Patent No. GB 2833375B	Voltage			
IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 2 4x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 4 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 4 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature 5* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Patents and Trademarks CPX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea Pick St. is a Registered Trade Mark No 2398667 Patent No. GB 2383375B It is the policy of the company t	Maximum Load	10 Amp inductive		
Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature 5° to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398667 Patent No. GB 238375B Linea is a Registered Trade Mark No 2398667 Patent No. GB 238375B Terminal Capacity 3 SE = 3021174 All products listed conform to current British or European standard and the product Information is BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as a part of our developm				
Terminal Capacity 1	IP Rating	IP2XD		
Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 4 x 1 x 6mm2 Fecommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398665 European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. But to manufactured under an accredited European standard and the product information is correct at the time of going to press. Due to manufactured under an accredited as a pa containing of our development programms Therefore, we reserve the right to alter designs and dimensions without prior notices. EXCE	·			
Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 3 *** to +40 *** C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Bas EN 60669-1 Linea is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398667 Patent No. GB ≥383375B Linea is a Registered Trade Mark No 2398665 CPX is a Registered Trade Design Certificate No: R2 = 3021173 SS2 = 3021174 Linea is a Registered Trade Mark No 2398665 European standard the product information is correct at the time of going to press. B EN 60001: 2015 Quality Management System. B EN 60001: 2015 Quality Management System. B EN 60001: 2015 Quality Management System. B Due to manufacturing processes we cannot the limitations of reproduction and printing processes and are not binding processes and are not binding processes and are not binding of certificate and standings of certificate and standings of and the product information is exact colour match and shadings of a certain first processes and are not binding the processes and are not binding and are not binding the processes and are not binding the proce	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4				
Terminal Capacity 5	Terminal Capacity 3			
Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks CPX is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CPX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bue to manufacturing processes we cannot guarantee an exact colour manufacturing shadings of Correct as at 15 October 2018 08:19 AM E&CE	Terminal Capacity 4			
Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 28383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BLINEATOR OF AUGUSTAN AND AUGUSTAN AN	Terminal Capacity 5			
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:19 AM E&OE	Earth Terminal Capacity 1			
Earth Terminal Capacity 4	Earth Terminal Capacity 2			
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. BUILUSTATIONS and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:19 AM E&OE	Earth Terminal Capacity 3			
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Bue to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not binding. Correct as at 15 October 2018 08:19 AM E&OE	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:19 AM E&OE	Earth Terminal Capacity 5			
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. But to the product information is as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:19 AM guarantee an exact colour match and shadings of of certain finishes.				
Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:19 AM guarantee an exact colour match and shadings of of certain finishes.	Ambient Operating Temperature			
Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BIllustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:19 AM E&OE		·		
Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.				
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Ullustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Standard/Approval			
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:19 AM E&OE	Patents and Trademarks	ents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of of certain finishes.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 15 October 2018 08:19 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio