

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

| LDR232BK-BKB | | |
|---|---|---|
| Linea-Duo CFX Black Nicke | el Frame/Black Nickel Front 3 gang 20AX 2 Wa | ay Rocker Black Nickel/Black |
| Item Image | Wiring | Dimensions |
| | | Hamilton LINEA DUO CFX R232 2 Way Rocker |
| | Adamatice 2 way sentang Lore in Lore Out | 145.0 |
| Primary Range | Linea-Duo CFX | |
| Insert Type | 3 gang 20AX 2 Way Rocker | |
| Plate Finish | Linea-Duo CFX Black Nickel Frame/Black Nickel | |
| Insert Colour | Black Nickel/Black | |
| EAN13 Barcode | 5017504232382 | |
| Dimensions (Nominal) | Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | Single | |
| Current Rating | 20AX | |
| Voltage | 220/250V AC | |
| Maximum Load | 20 Amp inductive | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 5 x 1mm2 | |
| Terminal Capacity 2 | 4 x 1.5mm2 | |
| Terminal Capacity 3 | 2 x 2.5mm2 | |
| Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Terminal Capacity 5 | 1 x 6mm2 | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| | 5 x 1.5mm2 | |
| Earth Terminal Capacity 2 Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| 1 , | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 4 | | |
| Earth Terminal Capacity 5 | 1 x 6mm2 Must be earthed | |
| Product Class 1 | | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval Patents and Trademarks | BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 08:20 AM E&OE |
| | | riba bei Iso |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio