

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDR23PB-PBB

Item Image Attended 2 way seekings	<u>LDR23PB-PBB</u> Linea-Duo CFX Polished Brass Frame/Polished Brass Front 3 gang 10AX 2 Way Rocker Polished Brass/Black		
Attenuate 2 way seldang	Wiring	Dimensions	
Attenuate 2 way seldang		Hamilton	
Attenuate 2 way seldang		LINEA DUO CFX R23	
Attenuate 2 way seldang	Alternative 2 way switching	2 Way Rocker	
		86.0	
y Range Linea-Duo CFX			
Insert Type 3 gang 10AX 2 Way Roo	3 gang 10AX 2 Way Rocker		
Plate Finish Linea-Duo CFX Polished	Linea-Duo CFX Polished Brass Frame/Polished Brass		
Insert Colour Polished Brass/Black	Polished Brass/Black		
EAN13 Barcode 5017504102234	5017504102234		
Dimensions (Nominal) Single: Height = 86.0m	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm		
Fixing Hole Centres Box Fixing = 60.3mm G	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth 25mm	25mm		
Switched Poles Single	Single		
Current Rating 10AX	10AX		
Voltage 220/250V AC	220/250V AC		
Maximum Load 10 Amp inductive	10 Amp inductive		
Mains Frequency 50Hz	50Hz		
IP Rating IP2XD	IP2XD		
Contact Gap Minimum 3mm	3mm		
Terminal Capacity 1 5 x 1mm2	5 x 1mm2		
minal Capacity 2 4 x 1.5mm2			
Terminal Capacity 3 1 x 2.5mm2			
Terminal Capacity 4 1 x 4mm2 Multi-strand	1 x 4mm2 Multi-strand		
Terminal Capacity 5 1 x 6mm2	1 x 6mm2		
Earth Terminal Capacity 1 5 x 1mm2			
Earth Terminal Capacity 2 4 x 1.5mm2	4 x 1.5mm2		
Earth Terminal Capacity 3 3 x 2.5mm2	3 x 2.5mm2		
Terminal Capacity 4 1 x 4mm2 Multi-strand			
Earth Terminal Capacity 5 1 x 6mm2	rminal Capacity 5 1 x 6mm2		
Product Class 1 Must be earthed			
mbient Operating Temperature -5° to +40°C			
Recommended Location Internal Use Only			
Maximum Installation Altitude 2000m			
Standard/Approval BS EN 60669-1			
Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174			
	anufactured under an accredited	It is the policy of the company to improve products as part of our development programme.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufa guarantee an exa of	15 Quality Management System.	Therefore, we reserve the right to alter designs and dimensions without prior notice.	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio