

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

	LDR242BK-BKB			
Primary Range Unea-Duo CFX Intent Type 4 gang 20XX 2 Wey Rocker Unea-Duo CFX Block Nobel Frame-Block Nobel Intent Coolur Block Nobel Block EAN 158 Bordod 01756-04232090 Dimensions (Normal) Floor plot Centres Box Fixing - 120.6 from Grid Fixing - CFX Clips Minimar Wall Bloc Centres Box Fixing - 120.6 from Grid Fixing - CFX Clips Minimar Wall Bloc Centres Box Fixing - 120.6 from Grid Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - 120.6 from Grid Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - 120.6 from Grid Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - 120.6 from Grid Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - CFX Clips Minimar Mall Bloc Centres Box Fixing - CFX Clips Minimar Mall Block Centres Box Fixing - CFX Clips Minimar Mall Block Centres Box Fixing - CFX Clips Minimar Mall Block Centres Box Fixing - CFX Clips Minimar Mall Block Centres Box Fixing - CFX Clips Minimar Mall Block Centres Box Fixing - CFX Clips Minimar Mall Block Centres Box Fixing - CFX Clips Minimar Mall Block Centres Box Fixing - CFX Clips Minimar Mall Block Centres Box Fixing - CFX Clips Minimar Mall Block Centres Box Fixing - CFX Clips Box Fixing - CFX	Linea-Duo CFX Black Nickel Frame/Black Nickel Front 4 gang 20AX 2 Way Rocker Black Nickel/Black			
Primary Range Linea Duo CFX Insert Type 4 gang 20AX 2 Way Rocker Plate Finish Linear Coorur Back Nakel Michael Frame/Black Nickel Insert Type 1 days 20AX 2 Way Rocker Plate Finish Linear Coorur Back Nakel Michael Frame/Black Nickel Insert Coorur Back Nakel Black BAN13 Barcode Dimensions (Nominal) Double: Height = 68.0mm. Width = 145.0mm. Depth = 4.0mm Paing Holl Centres Back Rivaled Black Ban13 Barcode Dimensions (Nominal) Double: Height = 68.0mm. Width = 145.0mm. Depth = 4.0mm Back Rivaled Black Ban13 Barcode Dimensions (Nominal) Back Rivaled Black Ban13 Barcode Ban14 Ban13 Ban2 Ban14 B				
Primary Range Linea-Duo CFX Insert Type 4 gung 20AX 2 Way Rocker Plate Finish Linea-Duo CFX Black Nickel Frame-Black Nickel Insert Colour Black Nickel Black Nickel Frame-Black Nickel Insert Colour Black Nickel Black Nickel Black Nickel Black Nickel Rept EAN1 8 Barcode 5017504232389 EAN1 8 Barcode 5017504232389 Demensions (Nominal) Double: Height = 8 Gnm Width = 145.0mm Depth = 4.0mm Princy Holo Centres 8x Fining = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Dopth 3xmm Siminum Vall Box Dopth 3xmm Siminum Load 3x Fining = 120.6mm Grid Fixing = CFX Clips Minimum Vall Box Dopth 3xmm Minimum Capacity 5x Fining 120.0mm Prating Capacity 120.0mm Prating Capacity 120.0mm Prating Capacity			R242	
Insert Type		Alternative 2 very sentating		
Pate Finish Linear-Clour Black Nickell Finance Clour Black Nickell Finance Black Nickell Black EAN13 Barcode 5017504223399 Densions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Current Rating 20AX Voltage 220250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz PRating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 6 Earth Terminal C	Primary Range	Linea-Duo CFX		
Insert Colour Black Nickel/Black S017504/232399 Doubles (Nominal) Double Height = 86.0mm Width = 145.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth S5mm S5mm S5mm S6mm S6mm S6mm S6mm S6mm	Insert Type	4 gang 20AX 2 Way Rocker		
EAN13 Barcode Sol7504232399 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.8mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 2207250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x tmm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4 mm2 Earth Terminal Capacity 5 5 x 1 mm2 Earth Terminal Capacity 5 5 x 1 mm2 Earth Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 4 2 x 4 mm2 Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth T	Plate Finish	Linea-Duo CFX Black Nickel Frame/Black Nickel		
Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Dapth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall box Depth Switched Potes Single Current Rating 20AX Voltage 202050V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz PRating Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Ear	Insert Colour	Black Nickel/Black		
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips	EAN13 Barcode	5017504232399		
Minimum Wall Box Depth Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz Fating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 1 5 x 1 x 5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 Line is a Registered Trade Mark No 239865 CFX is a Registered Trade Mark No 239865 Therefore, we reserve he right to alter designs and dimensions without prior notice. Exception and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of ortertin finisher. Exceptions and diagrams are reproduced within the limitations of reproduction and printing processes we cannot binding.	Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm		
Switched Poles Current Rating 20AX Voltage 220/250V AC Maximum Load 220 Amp inductive Mains Frequency 50Hz IP Rating IP SXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 9 Earth Terminal Cap	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Current Rating 20AX Voltage 220/250V AC Maximum Load 22 Amp inductive Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 7 x 6mm2 Earth Terminal Capacity 9 7 x 6mm2 Earth Terminal Capacity 9 8 x 1 x 6mm2 Earth Terminal Capacity 9 8 x 8 x 8 x 8 x 8 x 8 x 8 x 8 x 8 x 8	Minimum Wall Box Depth	35mm		
Voltage 220/250V AC Maximur Load 20 Amp inductive Maxims Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 1 5x 1mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 1x 6mm2 Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 6 5x 1.5mm2 Earth Terminal Capacity 8 3x 2.5mm2 Earth Terminal Capacity 9 5x 1.5mm2 Earth Terminal Capacity 9 1x 6mm2 Earth Terminal Capacity 9 1x 6mm2 Earth Terminal Capacity 9 1x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature 5° 10 + 40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60689-1 Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CPA is a Registered Design Certificate No. R21 = 3021173 SS2 = 3021174 It is the policy of the company to improve products a part of our development programme. The referoe, we reserve the right to latter designs and dimensions without prior notice. BILIDITATION OF THE AMERICAN OF THE PROPOLET	Switched Poles	Single		
Maximum Load 20 Amp inductive Softz PRating Somma Somma	Current Rating	20AX		
Mains Frequency Pating P2XD	Voltage	220/250V AC		
P Rating	Maximum Load	20 Amp inductive		
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Z x 1.5mm2 Terminal Capacity 4 Z x 4mm2 Multi-strand Terminal Capacity 5 Larth Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 X x 2.5mm2 Earth Terminal Capacity 3 X x 2.5mm2 Earth Terminal Capacity 3 X x 2.5mm2 Earth Terminal Capacity 4 Z x 4mm2 Multi-strand Earth Terminal Capacity 5 Larth Terminal Capacity 6 Larth La	Mains Frequency	50Hz		
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 55 to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2	IP Rating	IP2XD		
Terminal Capacity 2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BALL Correct as at 15 October 2018 08-20 AM EACE Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certificate is a 15 October 2018 08-20 AM EACE Correct as at 15 October 2018 08-20 AM EACE Correct as at 15 October 2018 08-20 AM EACE	Contact Gap Minimum	3mm		
Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a Uk Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. But to manufacturing processes we cannot guarantee an exact colour match and shadings of correct as at 15 October 2018 08:20 AM E&OE	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 5 It x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BILUSTRATIONS and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Terminal Capacity 3	2 x 2.5mm2		
Earth Terminal Capacity 1	Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 7-5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BEN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of orerain finishes. Correct as at 15 October 2018 08:20 AM E&OE	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BY It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BY It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BY It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BY It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BY It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:20 AM guarantee an exact colour match and shadings of of certain finishes.	Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. BUUSTRAINGS AND	Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:20 AM E&OE	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:20 AM E&OE	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:20 AM E&OE	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location	Product Class 1	Must be earthed		
Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Ullustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:20 AM E&OE	Recommended Location	Internal Use Only		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Cryx is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:20 AM E&OE of certain finishes.	Maximum Installation Altitude	2000m		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:20 AM E&OE of certain finishes.	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:20 AM E&OE	Patents and Trademarks	Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of certain finishes.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 15 October 2018 08:20 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio