

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

the limitations of reproduction and printing guarantee an exact colour match and shadings of E&C	LDR24BC-BKB			
Primary Range Linea-Duo CFIX Insert Type 9 d. gang 10xX 2 Way Roover Insert Type 9 d. gang 10xX 2 Way Roover Insert Type 9 d. gang 10xX 2 Way Roover Insert Type 9 d. gang 10xX 2 Way Roover Insert Colors EARLY 3 Barcoder Desire Colors EARLY 3 Barcoder Desire Rooman State Soft France Rooman State	Linea-Duo CFX Bright Chrome Frame/Black Nickel Front 4 gang 10AX 2 Way Rocker Bright Chrome/Black			
Primary Range Linea-Duo CFX Insert Type 4 ageng LOX X Way Rocker Insert Type 4 ageng LOX X Way Rocker Plate Finish Linea-Duo CFX Bright Chrome Frame-Black Nobel Plates Finish Linea-Duo CFX Bright Chrome Frame-Black Nobel Plates Finish Linea-Duo CFX Bright Chrome-Black Nobel Double: Height - 86 mm Whith = 145 mm Depth = 4.0mm Double: Height - 86 mm Whith = 145 mm Depth = 4.0mm Double: Height - 86 mm Whith = 145 mm Depth = 4.0mm Double: Height - 86 mm Depth - 4.0mm D	Item Image	Wiring	Dimensions	
Primary Range Insert Type 4 gang 10AX 2 Way Rocker Insert Type 4 gang 10AX 2 Way Rocker Insert Type 4 gang 10AX 2 Way Rocker Insert Colour Bright Chrome-Black EAN13 Barcode 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 5017504092245 50175040924			R24	
Insert Type		Abernativa 2 rays weathing		
Plate Finish Linea-Duo CFX Bright Chrome Frame(Black Nickel	Primary Range	Linea-Duo CFX		
Bright Chrome/Black S017504982245 S017504982245 Box Fixing + 198.0mm Width = 145.0mm Depth = 4.0mm	Insert Type	4 gang 10AX 2 Way Rocker		
EAN13 Barcode 5017504092245 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum 3mm P2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4 mm2 Multi-strand Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 1 x 6mm	Plate Finish	Linea-Duo CFX Bright Chrome Frame/Black Nickel		
Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm Fixing Pole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz Frequency 50Hz Contact Gap Minimum 3mm Ferminal Capacity 1 5 x 1mm2 Ferminal Capacity 1 5 x 1mm2 Ferminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Ferminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 3 1 x 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 4 x 1.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Ea	Insert Colour			
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating 1P2XD Contact Gap Minimum 3mm Ferminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 9 Earth	EAN13 Barcode	5017504092245		
Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 3 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 5x 1mm2 Earth Terminal Capacity 5 5x 1x 5	Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm		
Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating 1P2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Cap	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Current Rating 10AX 200/250V AC 200/250V AC 200/250V AC 320/250V A	Minimum Wall Box Depth	25mm		
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 5 x 1 mm2 Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1	Switched Poles	Single		
Maximum Load Mains Frequency Sortz IP Rating IP2XD Contact Gap Minimum Smm Terminal Capacity 1 Sx 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Sx 1mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 Sx 1mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Ix 4mm2 Multi-strand Earth Terminal Capacity 3 Earth Terminal Capacity 4 Ix 4mm2 Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Termin	Current Rating	10AX		
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-istrand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 1x 4mm2 Multi-istrand Earth Terminal Capacity 3 1x 4mm2 Multi-istrand Earth Terminal Capacity 3 1x 6mm2 Earth Terminal Capacity 4 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 EXCOMPANIENT OF The DEVELOPMENT Of The Developmen	Voltage	220/250V AC		
IP Rating	Maximum Load	10 Amp inductive		
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Ambient Operating Temperature Ambient Operating Temperature 7.5° to +40°C Recommended Location Maximum Installation Altitude Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product indomation is correct at the time of going to press. All products listed conform to current British or European standard and the product indomation is correct at the time of going to press. BA (All products listed conform to current British or European standard and the product indomation is correct at the time of going to press. BA (All products listed conform to current British or European standard and the product indomation is correct at the time of going to press. BA (All products listed conform to current British or European standard and the product indomation is correct at the time of going to press. BA (All products listed conform to current British or European standard and the product indomation is correct at the time of going to press. BA (Ba (Capacity A) All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System Therefore, we reserve the right to alter designs and dimensions without prior notice. BA (Carrent A) BA (Carrent	Mains Frequency	50Hz		
Terminal Capacity 2 1 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 8 commended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60699-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Due to manufacturing processes we cannot Therefore, we reserve the right to alter designs and dimensions without prior motice. Therefore, we reserve the right to alter designs and dimensions without prior motice. Due to manufacturing processes we cannot Correct as at 15 October 2018 08:20 / EXC	IP Rating	IP2XD		
Terminal Capacity 2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 1 x 4mm2 Multi-strand Earth Terminal Capacity 6 Earth Terminal Capacity 7 I x 4mm2 Multi-strand Earth Terminal Capacity 8 Earth Terminal Capacity 9 I x 4mm2 Multi-strand Earth Terminal Capa	Contact Gap Minimum	3mm		
Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 T x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufacted under an accredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BN Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4 1 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BEEN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior rodice. BUILUstrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 FEX.	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A Example 1.	Terminal Capacity 3	1 x 2.5mm2		
Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A E&C	Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Blustrations and diagrams are reproducted within the limitations of reproduction and printing guarantee an exact colour match and shadings of Eact 1 Ax 1.5mm2 1 x 4mm2 Multi-strand 2 x 2.5mm2 1 x 4mm2 Multi-strand 2 x 20mm2 Eact 2 x 4 x 1.5mm2 1 x 4mm2 Multi-strand 2 x 4 x 1.5mm2 1 x 4mm2 Multi-strand 2 x 4 x 1.5mm2 4 x 1.5mm2 2 x 4 x 1.5mm2	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A guarantee an exact colour match and shadings of Correct as a contract and correct as a contract and correct and correct as a correct as a correct as a correct and correct as a	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Must be earthed Jone 1 Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Correct as at 15 October 2018 08:20 A Earth Countries and shadings of Earth Coun	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to manufacturing processes we cannot the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A EXCEPTION TO THE PROPERTY OF THE PR	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A E&C.	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of EXCENTION TO THE TO	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A E&C.	Product Class 1	Must be earthed		
Maximum Installation Altitude Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A E&C.	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A E&C.	Recommended Location	Internal Use Only		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:20 A guarantee an exact colour match and shadings of	Maximum Installation Altitude	2000m		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. BUUstrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:20 A E&C	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&C	Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B			
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&C	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
Plusible 4 Out Heide Conid Davis and Control of Davis and District Property Post Plusible 2 Out Heide Conid Davis As Dav			Correct as at 15 October 2018 08:20 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio