

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LDR26PB-ABB

Item Image	Wiring	Dimensions
		Hamilton LINEA DUO CFX
		R26 2 Way Rocker
	Abstraction 2 way switching  Loss pi Lone Out  Transmission a way switching  Abstraction 2 way switching	145.0
Primary Range	Linea-Duo CFX	
nsert Type	6 gang 10AX 2 Way Rocker	
Plate Finish	Linea-Duo CFX Polished Brass Frame/Antique Brass	
nsert Colour	Polished Brass/Black	
EAN13 Barcode	5017504122201	
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	25mm	
Switched Poles	Single	
Current Rating	10AX	
/oltage	220/250V AC	
Maximum Load	10 Amp inductive	
Mains Frequency	50Hz	
P Rating	IP2XD	
Contact Gap Minimum	3mm	
Ferminal Capacity 1	5 x 1mm2	
Ferminal Capacity 2	4 x 1.5mm2	
Ferminal Capacity 3	1 x 2.5mm2	
Ferminal Capacity 4	1 x 4mm2 Multi-strand	
erminal Capacity 5	1 x 6mm2	
arth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
flaximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB Linea-Duo CFX is a UK Registered Design Certificate No: R2	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:20 of E&

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio