

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDR26SN-BSW			
Linea-Duo CFX Satin Nick	el Frame/Bright Steel Front 6 gang 10AX 2 Wa	ay Rocker Satin Steel/White	
Item Image	Wiring	Dimensions	
		Hemilton LINEA DUO CFX R26 2 Way Rocker	
	Adminish 2 very sentaining Long in Long Out Sentencials sentaining	145.0 145.0 150.2 In	
Primary Range	Linea-Duo CFX		
Insert Type	6 gang 10AX 2 Way Rocker	6 gang 10AX 2 Way Rocker	
Plate Finish	Linea-Duo CFX Satin Nickel Frame/Bright Steel		
Insert Colour	Satin Steel/White		
EAN13 Barcode	5017504307202		
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	25mm		
Switched Poles	Single		
Current Rating	10AX		
Voltage		220/250V AC	
Maximum Load	10 Amp inductive		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	3mm		
Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 3	1 x 2.5mm2		
Terminal Capacity 4	1 x 4mm2 Multi-strand		
Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 1	5 x 1mm2		
	4 x 1.5mm2		
Earth Terminal Capacity 2 Earth Terminal Capacity 3	3 x 2.5mm2		
1 ,	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	Must be earthed		
Product Class 1			
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval Patents and Trademarks	BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:20 AM E&OE	
		ribe bei 150	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio