

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDR32SN-SSB Linea-Duo CFX Satin Nickel Frame/Satin Steel Front 2 gang 10AX Intermediate Rocker Satin Steel/Black Item Image Wiring **Dimensions** Hamilton 2 Way Switch 2 Way Switch R32 Intermediate Rocker Linea-Duo CFX Primary Range Insert Type 2 gang 10AX Intermediate Rocker Plate Finish Linea-Duo CFX Satin Nickel Frame/Satin Steel Insert Colour Satin Steel/Black EAN13 Barcode 5017504226329 Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single **Current Rating** 10AX 220/250V AC Voltage 10 Amp inductive Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 **Terminal Capacity 3** 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Internal Use Only Recommended Location Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All accessories are manufactured under an accredited All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001: 2015 Quality Management System. as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 15 October 2018 08:21 AM E&OE guarantee an exact colour match and shadings of the limitations of reproduction and printing process and are not binding.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio