SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LDSATICB-CBB

Linea-Duo CFX Copper Bronze Frame/Copper Bronze Front 1 gang Isolated Satellite Black

| Linea-Duo CFX Copper Bronze Frame/Copper Bronze Front 1 gang Isolated Satellite Black   |  |  |
|---|--|--|
| Item Image  | Wiring  Single Terminal Clamp  | Dimensions  Hemilton LINEA DUO CFX SATI Non-Isolated Satellite   |
| Primary Range   | Linea-Duo CFX  |  |
| Insert Type   | 1 gang Isolated Satellite  |  |
| Plate Finish  | Linea-Duo CFX Copper Bronze Frame/Copper Bronze  |  |
| Insert Colour   | Black  |  |
| EAN13 Barcode   | 5017504041168  |  |
| Dimensions (Nominal)  | Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm   |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |  |
| Minimum Wall Box Depth  | 35mm   |  |
| Switched Poles  | N/A  |  |
| IP Rating   | IP2XD  |  |
| Contact Gap Minimum   | N/A  |  |
| Earth Terminal Capacity 1   | 5 x 1mm2   |  |
| Earth Terminal Capacity 2   | 4 x 1.5mm2   |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2   |  |
| Earth Terminal Capacity 4   | 1 x 4mm2 Multi-strand  |  |
| Earth Terminal Capacity 5   | 1 x 6mm2   |  |
| Product Class 1   | Must be earthed (ref BS7671 415.2.1)   |  |
| Ambient Operating Temperature   | -5° to +40°C   |  |
| Recommended Location  | Internal Use Only  |  |
| Maximum Installation Altitude   | 2000m  |  |
| EuroFix Additional Notes  | Isolated F-type outlet for Satellite or Cable TV installations where a DC signal back to the LNB unit on the satellite dish NOT required.  |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.  Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 15 October 2018 08:21 AM<br>E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











