

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **LDSHSBC-SSW**

Item Image    Wirring   Dimensions	Linea-Duo CFX Bright Chrome Frame/Satin Steel Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White				
Primary Range Lines-Duo CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Insert Colour White Inser	Item Image	Wiring	Dimensions		
Insert Type	230 119		SHS		
Plate Finish   Linea-Duo CFX Vertical Bright Chrome Frame/Satin Steel	Primary Range	Linea-Duo CFX			
Insert Colour	Insert Type				
EAN13 Barcode   5017504210038   Dimensions (Nominal)   Double: Height = 145.0mm   Width = 86.0mm   Depth = 4.0mm   Fixing Hole Centres   Box Fixing = 120.6mm   Grid Fixing = CFX Clips   Minimum Wall Box Depth   47mm   Switched Poles   None   Current Rating   20VA   Voltage   220/250V AC	Plate Finish	Linea-Duo CFX Vertical Bright Chrome Frame/Satin Steel			
Dimensions (Nominal)   Double: Height = 145.0mm Width = 86.0mm Depth = 4.0mm	Insert Colour				
Fixing Hole Centres	EAN13 Barcode	5017504210038			
Minimum Wall Box Depth         47mm           Switched Poles         None           Current Rating         20VA           Voltage         220/250V AC           Maximum Load         200/250V input; 115/230V 20VA output           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Froduct Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573		- '			
Switched Poles         None           Current Rating         20VA           Voltage         220/250V AC           Maximum Load         200/250V input; 115/230V 20VA output           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips			
Current Rating         20VA           Voltage         220/250V AC           Maximum Load         200/250V input; 115/230V 20VA output           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573	-				
Voltage         220/250V AC           Maximum Load         200/250V input; 115/230V 20VA output           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40° C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573					
Maximum Load         200/250V input; 115/230V 20VA output           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573					
Mains Frequency       50Hz         IP Rating       IP2XD         Contact Gap Minimum       None         Terminal Capacity 1       5 x 1mm2         Terminal Capacity 2       4 x 1.5mm2         Terminal Capacity 3       3 x 2.5mm2         Terminal Capacity 4       2 x 4mm2 Multi-strand         Terminal Capacity 5       1 x 6mm2         Earth Terminal Capacity 1       9 x 1mm2         Earth Terminal Capacity 2       6 x 1.5mm2         Earth Terminal Capacity 3       4 x 2.5mm2         Earth Terminal Capacity 4       2 x 4mm2 Multi-strand         Earth Terminal Capacity 5       1 x 6mm2         Product Class 1       Must be earthed         Ambient Operating Temperature       -5° to +40°C         Recommended Location       Internal Use Only         Maximum Installation Altitude       2000m         Standard/Approval       BS EN 61558-2-5 - BS 4573					
IP Rating					
Contact Gap Minimum None  Terminal Capacity 1 5 x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 3 x 2.5mm2  Terminal Capacity 4 2 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 9 x 1mm2  Earth Terminal Capacity 2 6 x 1.5mm2  Earth Terminal Capacity 3 4 x 2.5mm2  Earth Terminal Capacity 4 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude  SEN 61558-2-5 - BS 4573	1 1				
Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573					
Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573	·				
Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573					
Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  9 x 1mm2  Earth Terminal Capacity 2  6 x 1.5mm2  Earth Terminal Capacity 3  4 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Earth Terminal Capacity 5  BS EN 61558-2-5 - BS 4573					
Terminal Capacity 5					
Earth Terminal Capacity 1 9 x 1mm2  Earth Terminal Capacity 2 6 x 1.5mm2  Earth Terminal Capacity 3 4 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 61558-2-5 - BS 4573					
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Earth Terminal Capacity 5  1 x 6mm2  Must be earthed  -5° to +40°C  Internal Use Only  BS EN 61558-2-5 - BS 4573					
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Earth Terminal Capacity 3  1 x 2.5mm2  1 x 6mm2  Must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  BS EN 61558-2-5 - BS 4573					
Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  2 x 4mm2 Multi-strand  1 x 6mm2  Must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  BS EN 61558-2-5 - BS 4573					
Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573					
Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 61558-2-5 - BS 4573					
Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 61558-2-5 - BS 4573					
Recommended Location     Internal Use Only       Maximum Installation Altitude     2000m       Standard/Approval     BS EN 61558-2-5 - BS 4573					
Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573					
Standard/Approval BS EN 61558-2-5 - BS 4573		·			
··					
Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm					
	Additional Notes	Must be mounted vertically. Shuttered :Yes. Box Depth 47mm			



SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio				
LDSHSBC-SSW				
Linea-Duo CFX Bright Chrome Frame/Satin Steel Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White				
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174			
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:21 AM E&OE		

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









