

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDSHSBK-BKB

Linea-Duo CFX Black Nickel Frame/Black Nickel Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black

Primary Range Linea-Duo CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Insert Colour Insert	Linea-Duo CFX Black Nickel Frame/Black Nickel Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black				
Primary Range Linea-Duo CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Linea-Duo CFX Vertical Black Nickel Frame/Black Nickel EAN13 Barcode S017504231033 Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fibring = 120.6mm Grld Fixing = CFX Clips Minimum Wall Box Depth 4/mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 220/250V input; 115/230V 20VA output Mains Frequency Braining P2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 5 x 4 x 2.5mm2 Earth Terminal Capacity 3 5 x 4 mm2 Multi-strand Earth Terminal Capacity 3 5 x 4 x 2.5mm2 Earth Terminal Capacity 3 5 x 4 mm2 Multi-strand Earth Terminal Capacity 3 5 x 4 mm2 Multi-strand Earth Terminal Capacity 3 5 x 4 mm2 Multi-strand Earth Terminal Capacity 3 5 x 4 mm2 Multi-strand	Item Image	Wiring	Dimensions		
Insert Type	230V - 115V		SHS Shaver Dual Voltage Unswitched Socket (Vertical Mounted) 40 43.5		
Plate Finish	Primary Range	Linea-Duo CFX			
Insert Colour	nsert Type	Shaver Dual Voltage Unswitched Socket (Vertically Mounted)			
EAN13 Barcode 5017504231033 Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	Plate Finish	Linea-Duo CFX Vertical Black Nickel Frame/Black Nickel			
Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	nsert Colour				
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	EAN13 Barcode	5017504231033			
Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	Dimensions (Nominal)	Double: Height = 145.0mm Width = 86.0mm Depth = 4.0mm			
Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips			
Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	vlinimum Wall Box Depth				
Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	Switched Poles				
Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand					
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 5 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 5 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	/oltage				
IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand		200/250V input; 115/230V 20VA output			
Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand					
Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand		IP2XD			
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand					
Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand		5 x 1mm2			
Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand		4 x 1.5mm2			
Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand		3 x 2.5mm2			
Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand					
Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	· · ·	1 x 6mm2			
Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	Earth Terminal Capacity 1	9 x 1mm2			
Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	Earth Terminal Capacity 2	6 x 1.5mm2			
·	Earth Terminal Capacity 3	4 x 2.5mm2			
		2 x 4mm2 Multi-strand			
Earth Terminal Capacity 5 1 x 6mm2	Earth Terminal Capacity 5	1 x 6mm2			
Product Class 1 Must be earthed	Product Class 1	Must be earthed			
Ambient Operating Temperature -5° to +40°C	Ambient Operating Temperature	-5° to +40°C			
Recommended Location Internal Use Only	Recommended Location	Internal Use Only			
Maximum Installation Altitude 2000m	Vaximum Installation Altitude	2000m			
Standard/Approval BS EN 61558-2-5 - BS 4573	Standard/Approval				
Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm					



SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDSHSBK-BKB

Linea-Duo CFX Black Nickel Frame/Black Nickel Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black

Linea-Duo CFX Black Nickel Frame/Black Nickel Front Snaver Dual Voltage Unswitched Socket (Vertically Mounted) Black				
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174			
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 15 October 2018 08:21 AM E&OE		

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











