

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDSHSPB-PBW

Item Image	Wiring	Dimensions Hamilton	
2300	Noutral Exact	Hemilton LINEA DUO CFX SHS Shaver Dual Voltage Unswitched Socket (Vertical Mounted)	
Primary Range	Linea-Duo CFX		
Insert Type	Shaver Dual Voltage Unswitched Socket (Vertically Mounted)		
Plate Finish	Linea-Duo CFX Vertical Polished Brass Frame/Polished Brass		
Insert Colour	White		
EAN13 Barcode	5017504100032		
Dimensions (Nominal)	Double: Height = 145.0mm Width = 86.0mm Depth = 4.0mm		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	47mm		
Switched Poles	None		
Current Rating	20VA		
Voltage	220/250V AC		
Maximum Load	200/250V input; 115/230V 20VA output		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	None		
Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 3	3 x 2.5mm2		
	2 x 4mm2 Multi-strand		
Terminal Capacity 5	1 x 6mm2		
	9 x 1mm2		
1 1	6 x 1.5mm2		
1 1	4 x 2.5mm2		
	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Must be earthed		
Ambient Operating Temperature	-5° to +40°C		
	Internal Use Only		
	2000m		
Standard/Approval	BS EN 61558-2-5 - BS 4573		
	Must be mounted vertically. Shuttered :Yes. Box Depth 47mm	1	



SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio				
<u>LDSHSPB-PBW</u> Linea-Duo CFX Polished Brass Frame/Polished Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 15 October 2018 08:22 AM E&OE		

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











