

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDSHSPB-SBW

Primary Range Linea-Duo CFX Biser Daily Voltage Unswitched Socket (Vertically Mounted) Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Plate Finish Linea-Duo CFX Vertical Polished Brass Frame/Satin Brass Insert Colour White EAN13 Barcode 5017504110031 Double: Height = 145.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Cage Minimum None Ferminal Capacity 1 5 x 1mm2 Ferminal Capacity 1 5 x 1mm2 Ferminal Capacity 4 2 x 4mm2 Multi-strand Ferminal Capacity 4 1 9 x mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x mm2	Linea-Duo CFX Polished Brass Frame/Satin Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White			
Primary Range Linea-Duo CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Linea-Puo CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Linea-Puo CFX Vertical Polished Brass Frame/Satin Brass Insert Colour EAN13 Barcode So17504110031 Dimensions (Nominal) Dimensions (Nominal) Dimensions (Nominal) Dimensions (Nominal) Dimensions (Nominal) Pixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency SoHz IF Rating IP ZXD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 1 x 6mm2 Terminal Capacity 4 2 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Primary Range Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Linea-Duo CFX Vertical Polished Brass Frame/Satin Brass Insert Colour White EAN13 Barcode Soft7504110031 Dimensions (Nominal) Dimensions (Nominal) Piking Hole Centres Box Fixing = 120.6mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles Current Rating 20VA Voltage 220/250V AC Maximum Load Mains Frequency Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles Current Rating 120VA Voltage 220/250V AC Maximum Load Mains Frequency Fixing Hole Centres Soltz Switched Poles Current Rating 20VA Voltage 220/250V AC Maximum Load Mains Frequency Fixing IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 6mm2 Terminal Capacity 5 1 x 6mm2	LINEA DUO CFX SHS SHS Shaver Dual Voltage Unswitched Socket (Vertical Mounted)			
Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Plate Finish Linea-Duo CFX Vertical Polished Brass Frame/Satin Brass Insert Colour White EAN13 Barcode 5017504110031 Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2	5			
Plate Finish Linea-Duo CFX Vertical Polished Brass Frame/Satin Brass Insert Colour White EAN13 Barcode 5017504110031 Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Insert Colour White				
EAN13 Barcode 5017504110031 Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles Current Rating 20VA Voltage 220/250V AC Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Minimm Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2				
Terminal Capacity 5 1 x 6mm2				
Earth Terminal Capacity 1 9 x 1mm2				
Earth Terminal Capacity 2 6 x 1.5mm2				
Earth Terminal Capacity 3 4 x 2.5mm2				
Earth Terminal Capacity 4 2 x 4mm2 Multi-strand				
Earth Terminal Capacity 5 1 x 6mm2				
Product Class 1 Must be earthed				
	-5° to +40°C			
Recommended Location Internal Use Only				
	2000m			
	BS EN 61558-2-5 - BS 4573			
Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm				



SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio			
LDSHSPB-SBW			
Linea-Duo CFX Polished Brass Frame/	Satin Brass Front Shaver Dual Voltage Unsw	vitched Socket (Vertically Mounted) White	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 15 October 2018 08:22 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









