Hamilton

making connections beautifully

역 (가장 14 명원) 이 등 (강영영 (1883) (1983)	Wiring Accessories • Circuit Protection • Sr	mart Lighting Control & Multi-room Audio
LDSS1SB-SBW Linea-Duo CFX Satin Brass Frame/Satin Brass Front 1 gang 13A Double Pole Switched Socket Satin Brass/White		
Item Image	Wiring	Dimensions
	Neutral Earth Live	Hemilton LINEA DUO CFX SS1 Switched Socket
Primary Range	Linea-Duo CFX	
Insert Type	1 gang 13A Double Pole Switched Socket	
Plate Finish	Linea-Duo CFX Satin Brass Frame/Satin Brass	
Insert Colour	Satin Brass/White	
EAN13 Barcode	5017504153014	
	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm	
Dimensions (Nominal) Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
-	35mm	
Minimum Wall Box Depth Switched Poles	Double	
Current Rating	13 Amp 220/250V AC	
Voltage		
Maximum Load	13 Amp 50Hz	
Mains Frequency IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	4 x 2.5mm2	
	4 x 2.5mm2 3 x 4mm2	
Terminal Capacity 2	2 x 6mm2 Multi-Strand	
Terminal Capacity 3		
Terminal Capacity 4	1 x 10mm2	
Earth Terminal Capacity 1	4 x 2.5mm2	
Earth Terminal Capacity 2	3 x 4mm2	
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand	
Earth Terminal Capacity 4	1 x 10mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 1363-2	
Additional Notes	Dual Earth: Yes	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:22 A E&C
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville R T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered (E: info@hamilton-litestat.com www.hamilton-litestat.com Registered i	oad, Brislington, Bristol, BS4 5NZ office 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Trimble. LUCKINS Fieldor DisSPlus (BL No. M1128

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio