


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LDSS2SN-SSW

Linea-Duo CFX Satin Nickel Frame/Satin Steel Front 2 gang 13A Double Pole Switched Socket Satin Steel/White

Item Image









| Primary Range   | Linea-Duo CFX  |  |
|---|--|--|
| Insert Type   | 2 gang 13A Double Pole Switched Socket   |  |
| Plate Finish  | Linea-Duo CFX Satin Nickel Frame/Satin Steel   |  |
| Insert Colour   | Satin Steel/White  |  |
| EAN13 Barcode   | 5017504227029  |  |
| Dimensions (Nominal)  | Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm  |  |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = CFX Clips   |  |
| Minimum Wall Box Depth  | 35mm   |  |
| Switched Poles  | Double   |  |
| Current Rating  | 13 Amp   |  |
| Voltage   | 220/250V AC  |  |
| Maximum Load  | 13 Amp   |  |
| Mains Frequency   | 50Hz   |  |
| IP Rating   | IP2XD  |  |
| Contact Gap Minimum   | 3mm  |  |
| Terminal Capacity 1   | 4 x 2.5mm2   |  |
| Terminal Capacity 2   | 3 x 4mm2   |  |
| Terminal Capacity 3   | 2 x 6mm2 Multi-Strand  |  |
| Terminal Capacity 4   | 1 x 10mm2  |  |
| Earth Terminal Capacity 1   | 4 x 2.5mm2   |  |
| Earth Terminal Capacity 2   | 3 x 4mm2   |  |
| Earth Terminal Capacity 3   | 2 x 6mm2 Multi-strand  |  |
| Earth Terminal Capacity 4   | 1 x 10mm2  |  |
| Product Class 1   | Must be earthed  |  |
| Ambient Operating Temperature   | -5° to +40°C   |  |
| Recommended Location  | Internal Use Only  |  |
| Maximum Installation Altitude   | 2000m  |  |
| Standard/Approval   | BS 1363-2  |  |
| Additional Notes  | Dual Earth: Yes  |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing   | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes   | Correct as at 15 October 2018 08:22 AM E&OE  |

of certain finishes.

process and are not binding. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









LDSS2SN-SSW - Linea-Duo CFX Satin Nickel Frame/Satin Steel Front 2 gang 13A Double Pole Switched Socket Satin Steel/White





Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio