

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDT21PB-PB

Primary Range Lines-Duo CFX Insert Type I spring 200X 2 Ways Trougle Insert Strought 2 Wasses Insert Colour Fallshood Brass Fallshood Brass Fallshood Brass Fallshood Brass Fallshood Brass Insert Colour Fallshood Brass Fallshood	Linea-Duo CFX Polished Brass Frame/Polished Brass Front 1 gang 20AX 2 Way Toggle Polished Brass			
Primary Range Linea-Duo CFX Insert Type 1 garing 2004 X Way Troggle Insert Color Petits Fishin Linea Duo CFX Polished Brass Farmi Petitshed Brass Insert Color Petits Fishin Linea Duo CFX Polished Brass Farmi Petitshed Brass Insert Color Petits Fishin Linea Duo CFX Polished Brass Farmi Petitshed Brass Insert Color Petits Fishin Linea Duo CFX Polished Brass Farmi Petitshed Brass Insert Color Insert Color Petits Fishin Linea Duo CFX Color Insert Color Inse	Linea Duo Of A Folished Blass Frame/Folished Blass Front Figure 20AA 2 Way Toggle Folished Blass			
Primary Range Linear-Duo CFX Insert Type 1 gang 20X Z Way 190gg/e Plate Finish Unes-Duo CFX Polished Brass Frame/Polished Brass Insert Colour Polished Brass Rancede 5017504 10250 Plate Finish Rancede 5017504 Plate	Item Image	Wiring	Dimensions	
Primary Range Linear-Duo CFX Insert Type 1 gang 20X Z Way 190gg/e Plate Finish Unes-Duo CFX Polished Brass Frame/Polished Brass Insert Colour Polished Brass Rancede 5017504 10250 Plate Finish Rancede 5017504 Plate			• • • • • • • • • • • • • • • • • • •	
Primary Range Unea-Duo CPX Insert Type 1 gang 20X1 2 Way Toggle Phile Finish Unea-Duo CPX Polished Brass Insert Colour Polished Brass Single Single Height = 80.0mm. Width = 80.0mm. Depth = 4.0mm Polished Brass Single Control Single Depth = 4.0mm Switched Polise Single Minimum Well Box Depth Single Sing			Hamilton LINEA DUO CFX	
Primary Range Linea-Duo CFX Insert Type 1 gang 20AX 2 Way Toggle Plate Finish Linear Colour Polished Brass EAN13 Barnode 5017904102288 Dimensions (Nominal) Single: Height = 86 0mm Width = 86 0mm Depth = 4 0mm Fixing Holio Centros Box Fixing = 603 mm Width = 86 0mm Depth = 4 0mm Fixing Holio Centros Box Fixing = 603 mm Width = 86 0mm Depth = 4 0mm Fixing Holio Centros Box Fixing = 603 mm Grid Fixing = CFX Clips Minimum Wall Box Depth Samm Switched Potes Single Current Rating 200X Voltage 220250V AC Waiter Firequency Firequency Box Fixing = 603 mm Grid Fixing = CFX Clips Single Current Rating 200X Voltage 220250V AC Contact Gga Minimum Firequency 501-2 Firequency 501-2 Firequency 501-2 Firequency 501-2 Fireminal Capacity 1 5 x x mm2 Terminal Capacity 3 2 x 2.5 mm2 Terminal Capacity 4 2 x 4 mm2 Multi-strand Terminal Capacity 4 5 x 1.5 mm2 Earth Terminal Capacity 1 5 x 1.5 mm2 Earth Terminal Capacity 3 3 x 2.5 mm2 Earth Terminal Capacity 3 3 x 2.5 mm2 Earth Terminal Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 5 1 x 6 mm2 Fireduct Class 1 Abstract Capacity 6 Fireduct State of order to current Stiffs of the company to propose or a control of the company to propo			T21 2 Way Toggle	
Primary Range Linea-Duo CFX Insert Type 1 gang 2MAX 2 Way Toggle Plate Finish Linea-Culour Polished Brass Frame(Polished Brass Frame(Po		Death Live Noted	,	
Primary Range Insert Type Insert Colour Polished Brass Insert Colour Polished Brass EAN13 Barcode Solf7564192258 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fibring Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Somme Switched Poles Single Quarter Rating Quarter Rati		Dath is survey by the survey b	86.0	
Primary Range Insert Type Insert Colour Polished Brass Insert Colour Polished Brass EAN13 Barcode Solf7564192258 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fibring Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Somme Switched Poles Single Quarter Rating Quarter Rati		Control of the contro		
Primary Range Insert Type Insert Colour Polished Brass Insert Colour Polished Brass EAN13 Barcode Solf7564192258 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fibring Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Somme Switched Poles Single Quarter Rating Quarter Rati		Alternative 2 very sectoring		
Insert Type I gang 20AX 2 Way Toggle Linea-Duo CFX Polished Brass Linea-Duo CFX Polished Brass Insert Colour Polished Brass EAN13 Barcode 5017504102258 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 69.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 33mm Switched Poles Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP PZXD Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 6mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 Linear Terminal Capacity 5 Linear Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Ax 1.5mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Linear Multi-strand Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Linear Multi-strand Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Linear Multi-strand Earth Terminal Capacity 6 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Earth Terminal Capacity 8 Earth Earth No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate Nor. R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European sendated and the product information is colour and the information of the correlation and colour match and and plang of the corre		нистровое училину	86.0	
Insert Type I gang 20AX 2 Way Toggle Linea-Duo CFX Polished Brass Linea-Duo CFX Polished Brass Insert Colour Polished Brass EAN13 Barcode 5017504102258 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 69.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 33mm Switched Poles Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP PZXD Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 6mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 Linear Terminal Capacity 5 Linear Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Ax 1.5mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Linear Multi-strand Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Linear Multi-strand Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Linear Multi-strand Earth Terminal Capacity 6 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Earth Terminal Capacity 8 Earth Earth No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate Nor. R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European sendated and the product information is colour and the information of the correlation and colour match and and plang of the corre				
Insert Type				
Plaste Finish Linear-Duo CFX Polished Brass Frame/Polished Brass	Primary Range	Linea-Duo CFX		
Insert Colour Polished Brass EAN13 Barcode 5017504102288 University Fleight = 86.0mm Width = 86.0mm Depth = 4.0mm Single: Height = 86.0mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 220250V AC Maximum Load 20 Amp inductive Marine Frequency 50Hz IP Rating IP2XD Contact Cap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 8 x 1.5mm2 Earth Terminal Capacity 1 8 x 1.5mm2 Earth Terminal Capacity 1 8 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 S x 1.5mm2 Earth Terminal Capacity 6 S x 1.5mm2 Earth Terminal Capacity 6 S x 1.5mm2 Earth Terminal Capacity 7 S x 2.5mm2 Earth Terminal Capacity 8 S x 1.5mm2 Earth Terminal Capacity 8 S x 1.5mm2 Earth Terminal Capacity 9 S x 2.5mm2 Earth Terminal Capacity 1 S x 2.5mm2 Earth Terminal Capacity 1 S x 2.5mm2 Earth Terminal Capacity 1 S x 2.5mm2 Earth Terminal Capacity 6 S x 1.5mm2 Earth Terminal Capacity 6 S x 1.5mm2 Earth Terminal Capacity 7 S x 2.5mm2 Earth Terminal Capacity 8 S x 1.5mm2 Earth Terminal Capacity 8 S x 1.5mm2 Earth Terminal Capacity 9 S x 2.5mm2 Earth Terminal Capacity 1 S x 2.5m		1 gang 20AX 2 Way Toggle		
EAN13 Barcode 5017504102258 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Vottage 220250V AC Maximum Load 20 Amp Inductive Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Ferminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 4 mm2 Multi-strand Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 4 2 x 4 mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 8 2 x 4 mm2 Multi-strand Earth Terminal Capacity 9 2 x 4 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 6mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 6mm2 Earth Terminal Capacity 5 7 x 6mm2 Earth Terminal Capacity 6 x 1 x 6mm2 Earth Terminal Capacity 7 x 1 x 6mm2 Earth Terminal Capacity 8 x 1 x 6mm2 Earth Terminal Capacity 8 x 1 x 6mm2 Earth Terminal Capacity 9 x 1 x 6mm2 Earth Termi	Plate Finish	Linea-Duo CFX Polished Brass Frame/Polished Brass		
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Pixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Symn Switched Poles Single Current Rating 20AX Voltage 220/2550 V AC Maximum Load 20 Amp inductive Mains Frequency 10 Reting PPXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 4 mm2 Multi-strand Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Ca	Insert Colour	Polished Brass		
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Simple Current Rating 20AX Voltage 2202550V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x mm2 Terminal Capacity 1 5 x mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Ter	EAN13 Barcode	5017504102258		
Minimum Wall Box Depth 35mm Switched Poles 5ingle Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 1x 6mm2 Earth Terminal Capacity 4 5x 1mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 6x 1mm2 Earth Terminal Capacity 1 6x 1mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 4 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 6x 1x 6mm2 Earth Terminal Capa	Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm		
Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 x 6x 7 x 7 x 7 x 7 x 7 x 7 x 7 x 7 x	Minimum Wall Box Depth	35mm		
Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP	Switched Poles	Single		
Maximum Load Mains Frequency SoNz IP Rating IP2XD Contact Gap Minimum Smm Terminal Capacity 1 Sox 1mm2 Terminal Capacity 2 Terminal Capacity 2 Terminal Capacity 3 Zox 2.5mm2 Terminal Capacity 4 Zox 4mm2 Multi-strand Terminal Capacity 5 In x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Zox 4mm2 Multi-strand Terminal Capacity 3 Zox 1.5mm2 Earth Terminal Capacity 3 Zox 1.5mm2 Earth Terminal Capacity 3 Zox 1.5mm2 Earth Terminal Capacity 3 Zox 4mm2 Multi-strand Earth Terminal Capacity 3 Zox 4mm2 Multi-strand Earth Terminal Capacity 4 Zox 4mm2 Multi-strand Earth Terminal Capacity 5 Tox 6mm2 Earth Terminal Capacity 5 Tox 6mm2 Earth Terminal Capacity 5 Tox 6mm2 Earth Terminal Capacity 6 Internal Use only Maximum Installation Altitude Zox 4 mm2 Multi-strand Earth Terminal Capacity 6 Internal Use Only Maximum Installation Altitude Zox 4 mm2 Multi-strand Earth Terminal Capacity 6 Internal Use Only Maximum Installation Altitude Zox 4 mm2 Multi-strand Earth Terminal Capacity 6 Internal Use Only All products issed conform to current British or European standard and the product information is correct at the time of going to press. All products issed conform to current British or European standard and the product information is correct at the time of going to press. All accassories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Zox 4 mm2 All accassories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Earth Terminal Capacity 1 Earth	Current Rating			
Mains Frequency Pating	Voltage	220/250V AC		
IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 2 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 7 Terminal Capacity 8 Terminal Capacity 8 Terminal Capacity 9 Terminal Capacity 9	Maximum Load	20 Amp inductive		
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 Terminal Capacity 3 Terminal Capacity 4 2 x xmm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 To Manual Capacity 4 Earth Terminal Capacity 5 To Manual Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 To Manual Capacity 5 To Manual Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Ter	Mains Frequency	50Hz		
Terminal Capacity 2	IP Rating	IP2XD		
Terminal Capacity 2 1	Contact Gap Minimum	3mm		
Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BEN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 After the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 After the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 After the care and the product within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 After the care and the product within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 After the care and the product as a care of the care and the product of th	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4 2 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN 150 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. BS EN 150 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. END Use to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of EXO	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot the limitations of reproduction and printing Linea is a x 15 October 2018 08:22 Af Each Correct as at 15 Oct	Terminal Capacity 3	2 x 2.5mm2		
Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea-Duo CFX is a UK Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E&O	Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN 150 9001 : 2015 Quality Management System. But to the minimal Capacity 3 3 x 2.5mm2 2 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed -5° to +40°C Recommended Location Internal Use Only 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 All Each Colour match and shadings of	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Line Amm2 Patents Amm2 Linea-Duo CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BLUSTATION OF THE PROFICE, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 All E&O	Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 6069-1 Patents and Trademarks Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All coessories are manufactured under an accredited BS EN is a part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Bue to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 Al Earth Standard	Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 All correct as at 25 October 2018 08:22 All correct as 25 October 2018 08:22 All corre	Earth Terminal Capacity 3			
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 All E&O		2 x 4mm2 Multi-strand		
Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 All E&O				
Recommended Location				
Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 All E&O				
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of		·		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 Al E&O				
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:22 Al E&O	Standard/Approval			
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&O	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&O	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
F. Section and Strain			Correct as at 15 October 2018 08:22 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio