

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDT23PB-BS

Item Image Wiring Dimensions Hamiltoni Wiring Dimensions Dimensions Hamiltoni Wiring Dimensions Dimensions Dimensions Dimensions Dimensions	<u>LDT23PB-BS</u> Linea-Duo CFX Polished Brass Frame/Bright Steel Front 3 gang 20AX 2 Way Toggle Polished Brass			
Primary Range Linea-Duo CFX Insert Type 3 gang 2MA 2 Wij Toggle Primary Range Linea-Duo CFX Polished Breas Frame/Bright Steel Insert Color Polished Breas Box Framer 145 Omm Depth = 4.0mm Insert Bre				
Primary Range Insert Type 3 agang 20AX 2 Wey Toggle Plate Firish Insert Color Polished Brass Insert Color Polished Polish Insert Color Insert Color Insert Color Insert Color Polished Brass Insert Color			T23	
Insert Type 3 gang 20AX 2 Way Toggle Unea-Duc OFX Polished Brass Linea-Duc OFX Polished Brass EAN13 Barcode 5017504132279 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm Fishing Hole Centres Box Fixing = 120.0mm Grid Fixing = OFX Clips Minimum Wall Box Depth 35mm Switched Poles Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP PXD Contact Gap Minimum Terminal Capacity 1 5x x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 6x 1 1mm2 Earth Terminal Capacity 1 5x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 4x 1.5mm2 Earth Terminal Capacity 4 2x 4 mm2 Multi-strand 1x 6 mm2 Earth Terminal Capacity 5 1x 6 mm2 Earth Terminal Capacity 5 1x 6 mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 1 5x 1.5mm2 Earth Terminal Capacity 5 1x 6 mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 1x 6 mm2 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacit		Absention 2 very sectoring Long in Long Od Alternative 2 very sectoring		
Plate Finish Linser Colour Polished Brass Frame/Bright Steel Insert Colour Polished Brass Say Frame Plate Brain Steel Brain St	Primary Range	Linea-Duo CFX		
Plate Finish Linser Colour Polished Brass Frame/Bright Steel Insert Colour Polished Brass Say Frame Plate Brain Steel Brain St				
Foot	Plate Finish	1 1		
EAN13 Barcode S017504132279 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm				
Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm Fixing Holo Centres Box Fixing = 120.0mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 20AX Voltage 202050V AC Maximum Load 20 Amp Inductive Mains Frequency 50Hz PRating PRa				
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips				
Minimum Wall Box Depth Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency Finating PRating PRating Protect Forminal Capacity 1 So 1 Imm2 Terminal Capacity 1 So 1 Imm2 Terminal Capacity 1 So 1 Imm2 Terminal Capacity 2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 So 1 Imm2 Terminal Capacity 5 So 1 Imm2 Terminal Capacity 6 So 1 Imm2 Terminal Capacity 7 Terminal Capacity 6 So 1 Imm2 Imm3 So 1 Imm3 So 1 Imm3 So 2 Imm3 So 2 Imm3 So 2 Imm3 Imm3 So 2 Imm3 Imm3 So 2 Imm3 Imm3 So 2				
Switched Poles Current Rating 20AX Voltage 20250V AC Maximum Load 20 Amp inductive SoHz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 4.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 7 Earth Terminal Capacity 8				
Current Rating 20/X Voltage 220/ZSOV AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Ambient Operating Temperature 7.5 to +40 °C Recommended Location Maximum Installation Altitude Standard/Approval Bas EN 6069-1 Linea is a Registered Trade Mark No 2398667 CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All a coassories are manufactured under an accredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Bustrations and diagrams are reproducted within the limitations of reproduction and printing	•			
Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 1 5x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 4 2x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 6 1x 6mm2 Earth Terminal Capacity 7 1x 6mm2 Earth Terminal Capacity 8 1x 6mm2 Earth Terminal Capacity 9 1x 6mm2 Earth Terminal Capacity				
Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating				
Mains Frequency Frequ	-			
PRating IP2XD		 		
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Ax 1.5mm2 Terminal Capacity 3 Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Extherminal Capacity 5 Extherminal Capacity 4 Extherminal Capacity 4 Extherminal Capacity 5 Ix 6mm2 Extherminal Capacity 5 Ix 6mm2 Extherminal Capacity 4 Extherminal Capacity 4 Extherminal Capacity 5 Ix 6mm2 Extherminal Capacity 5 Ix 6mm2 Extherminal Capacity 6 Ix 6mm2 Extherminal Capacity 6 Exth				
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature 5 to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Business Registered Trade Mark No 2398667 Patent No. R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Business Registered Trade Mark No 2398668				
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 I x 6mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 I x 6mm2 Product Class 1 Must be earthed Albient Operating Temperature 5-5 to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BAI accessories are manufactured under an accredited SE NISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. BE EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. EEOR				
Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Z000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. BUL to manufacturing processes we cannot the limitations of reproduction and printing yourseless are accedited purpor and standings of Correct as at 15 October 2018 08:22 AM EROP Terminal Capacity 5 Exote Service Service American and shadings of Correct as at 15 October 2018 08:22 AM Earth Terminal Capacity 5 Exote Service Service American and shadings of Correct as at 15 October 2018 08:22 AM Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Ter				
Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tyoduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398667 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BS EN 50 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot Correct as at 15 October 2018 08:22 AM featured and an an exact colour match and shadings of Exception of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.				
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No Capacity 6 Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of				
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Earth Terminal Capacity 4 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand 2 x 4mm2 Multi-strand 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand 2 x 4mm2 Multi-strand 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 2 x 4mm2 Multi-strand Must be earthed 4 x 6mm2 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4				
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot the limitations of reproduction and printing quarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 AN Each Conformation and printing quarantee an exact colour match and shadings of				
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BS N ISO 9001 : 2015 Quality Management System. BUILUITATIONS and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 AM E&O				
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature So to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 AN Exception of the company to improve products and dimensions without prior notice.				
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 AN E&Ottober 2018 08:22 AN EXCENTINE 2015 08:22	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 AN E&OC	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Ugarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 AN E&Ottober 2018 08:22 AN EXAMPLE AND EACH CANNER OF THE PROPRIES OF THE	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 AN E&OC	Product Class 1			
Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Ullustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E&Ot	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:22 AN guarantee an exact colour match and shadings of	Recommended Location	Internal Use Only		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Lit is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:22 AN E&Of	Maximum Installation Altitude	2000m		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:22 AN E&OF	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot Correct as at 15 October 2018 08:22 AN E&OE E&OE	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	guarantee an exact colour match and shadings of E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio