



## LDTCSAB-ABB

### Linea-Duo CFX Antique Brass Frame/Antique Brass Front 1 gang Telephone Slave Black

Item Image	Wiring	Dimensions														
	<table border="1" data-bbox="662 472 964 604"> <thead> <tr> <th>Pin No.</th> <th>BT Wiring Schedule Colour Codes:</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Striped Wires GREEN / White</td> </tr> <tr> <td>2</td> <td>BLUE / White</td> </tr> <tr> <td>3</td> <td>ORANGE / White</td> </tr> <tr> <td>4</td> <td>WHITE / Orange</td> </tr> <tr> <td>5</td> <td>WHITE / Blue</td> </tr> <tr> <td>6</td> <td>WHITE / Green</td> </tr> </tbody> </table> <p data-bbox="673 604 953 611">Main Wire Colour shown in CAPITALS</p> <p data-bbox="711 613 915 663">Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.</p> <p data-bbox="662 688 964 762">The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel, ie Pin 1 to Pin 1 ; Pin 2 to Pin 2 ; etc. as shown in the diagram above.</p>	Pin No.	BT Wiring Schedule Colour Codes:	1	Striped Wires GREEN / White	2	BLUE / White	3	ORANGE / White	4	WHITE / Orange	5	WHITE / Blue	6	WHITE / Green	
Pin No.	BT Wiring Schedule Colour Codes:															
1	Striped Wires GREEN / White															
2	BLUE / White															
3	ORANGE / White															
4	WHITE / Orange															
5	WHITE / Blue															
6	WHITE / Green															
Primary Range	Linea-Duo CFX															
Insert Type	1 gang Telephone Slave															
Plate Finish	Linea-Duo CFX Antique Brass Frame/Antique Brass															
Insert Colour	Black															
EAN13 Barcode	5017504181659															
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm															
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips															
Minimum Wall Box Depth	25mm															
Switched Poles	N/A															
IP Rating	IP2XD															
Contact Gap Minimum	N/A															
Earth Terminal Capacity 1	5 x 1mm <sup>2</sup>															
Earth Terminal Capacity 2	4 x 1.5mm <sup>2</sup>															
Earth Terminal Capacity 3	3 x 2.5mm <sup>2</sup>															
Earth Terminal Capacity 4	1 x 4mm <sup>2</sup> Multi-strand															
Earth Terminal Capacity 5	1 x 6mm <sup>2</sup>															
Product Class 1	Must be earthed (ref BS7671 415.2.1)															
Ambient Operating Temperature	-5° to +40°C															
Recommended Location	Internal Use Only															
Maximum Installation Altitude	2000m															
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174															
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.														
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at 15 October 2018 08:23 AM E&OE														

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com



CERL No. FM1238