



LDTCSBC-SSB

Linea-Duo CFX Bright Chrome Frame/Satin Steel Front 1 gang Telephone Slave Black

| Item Image | Wiring | Dimensions | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|---|--------------------|---------------|---------------|--|--|---|---------------|--|---|--------------|--|---|----------------|--|---|----------------|--|---|--------------|--|---|---------------|--|--|
|  | <table border="1" data-bbox="662 470 964 600"> <thead> <tr> <th>Pin No.</th> <th>BT Wiring Schedule</th> <th>Colour Codes:</th> </tr> </thead> <tbody> <tr> <td colspan="3">Striped Wires</td> </tr> <tr> <td>1</td> <td>GREEN / White</td> <td></td> </tr> <tr> <td>2</td> <td>BLUE / White</td> <td></td> </tr> <tr> <td>3</td> <td>ORANGE / White</td> <td></td> </tr> <tr> <td>4</td> <td>WHITE / Orange</td> <td></td> </tr> <tr> <td>5</td> <td>WHITE / Blue</td> <td></td> </tr> <tr> <td>6</td> <td>WHITE / Green</td> <td></td> </tr> </tbody> </table> <p data-bbox="672 600 954 609">Main Wire Colour shown in CAPITALS</p> <p data-bbox="711 611 915 659">Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.</p> <p data-bbox="662 684 974 762">The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel, ie Pin 1 to Pin 1 ; Pin 2 to Pin 2 ; etc. as shown in the diagram above.</p> | Pin No. | BT Wiring Schedule | Colour Codes: | Striped Wires | | | 1 | GREEN / White | | 2 | BLUE / White | | 3 | ORANGE / White | | 4 | WHITE / Orange | | 5 | WHITE / Blue | | 6 | WHITE / Green | |  <p data-bbox="1235 464 1398 537">Hamilton® LINEA DUO CFX TCS Telephone Slave Socket</p> |
| Pin No. | BT Wiring Schedule | Colour Codes: | | | | | | | | | | | | | | | | | | | | | | | | |
| Striped Wires | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | GREEN / White | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | BLUE / White | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | ORANGE / White | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | WHITE / Orange | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | WHITE / Blue | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | WHITE / Green | | | | | | | | | | | | | | | | | | | | | | | | | |
| Primary Range | Linea-Duo CFX | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insert Type | 1 gang Telephone Slave | | | | | | | | | | | | | | | | | | | | | | | | | |
| Plate Finish | Linea-Duo CFX Bright Chrome Frame/Satin Steel | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insert Colour | Black | | | | | | | | | | | | | | | | | | | | | | | | | |
| EAN13 Barcode | 5017504211653 | | | | | | | | | | | | | | | | | | | | | | | | | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm | | | | | | | | | | | | | | | | | | | | | | | | | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | | | | | | | | | | | | | | | | | | | | | | | | | |
| Minimum Wall Box Depth | 25mm | | | | | | | | | | | | | | | | | | | | | | | | | |
| Switched Poles | N/A | | | | | | | | | | | | | | | | | | | | | | | | | |
| IP Rating | IP2XD | | | | | | | | | | | | | | | | | | | | | | | | | |
| Contact Gap Minimum | N/A | | | | | | | | | | | | | | | | | | | | | | | | | |
| Earth Terminal Capacity 1 | 5 x 1mm ² | | | | | | | | | | | | | | | | | | | | | | | | | |
| Earth Terminal Capacity 2 | 4 x 1.5mm ² | | | | | | | | | | | | | | | | | | | | | | | | | |
| Earth Terminal Capacity 3 | 3 x 2.5mm ² | | | | | | | | | | | | | | | | | | | | | | | | | |
| Earth Terminal Capacity 4 | 1 x 4mm ² Multi-strand | | | | | | | | | | | | | | | | | | | | | | | | | |
| Earth Terminal Capacity 5 | 1 x 6mm ² | | | | | | | | | | | | | | | | | | | | | | | | | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ambient Operating Temperature | -5° to +40°C | | | | | | | | | | | | | | | | | | | | | | | | | |
| Recommended Location | Internal Use Only | | | | | | | | | | | | | | | | | | | | | | | | | |
| Maximum Installation Altitude | 2000m | | | | | | | | | | | | | | | | | | | | | | | | | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 | | | | | | | | | | | | | | | | | | | | | | | | | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | | | | | | | | | | | | | | | | | | | | | | | | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. | Correct as at 15 October 2018 08:23 AM E&OE | | | | | | | | | | | | | | | | | | | | | | | | |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com



CERT. No. FM1238