SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


## **LDTVSATBC-BSB**

Linea-Duo CFX Bright Chrome Frame/Bright Steel Front 2 gang Non-Isolated TV+Satellite 2in/2out Black


Item Image







## **Dimensions**



| Plate Finish Linea-Duc CFX Bright Chrome Frame/Bright Steel Insert Colour Black EAN13 Barcode 5017504201685 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Minimum Wall Box Depth 35mm Minimum Wall Box Depth 37mm Minimum Wall Box Depth 35mm Minimum Wall Box Depth 35mm Minimum N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 2 4x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 4 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude  Patents and Trademarks CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No. R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard of the product information is correct at the time of going to press.  Base NiSo 3001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Business and diagrams are reproduced within the limitations of proproduction and printing guarantee an exact colour match ashadings of Englance and Scale of the Correct as at 15 October 2018 0823 guarantee an exact colour match ashadings of Englance and Scale of the Correct as at 15 October 2018 0823   | Primary Range                                    | Linea-Duo CFX  |  |
|--|--|--|--|
| Insert Colour  Black  EAN13 Barcode  5017504201685  Dimensions (Nominal)  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Switched Poles  N/A  IP Rating  IP2XD  Contact Gap Minimum  N/A  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Troduct Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Patents and Trademarks  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  Black  Soft Sa Bac.Omm Width = 86.0mm Depth = 4.0mm  Port Clips  Minimum Installation Altitude  Patents and Trademarks  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  Blustrations and diagrams are reproduced within the limitations of terproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 0823 guarantee an exact colour match and shadings of Correct as at 15 October 2018 0823   | Insert Type                                      | 2 gang Non-Isolated TV+Satellite 2in/2out                        |  |
| EAN13 Barcode  Dimensions (Nominal)  Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Switched Poles  IP2XD  Contact Gap Minimum  N/A  IP Rating  IP2XD  Contact Gap Minimum  N/A  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Patents and Trademarks  Patents and Trademarks  Linea-Duo CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Buerosen standard and the production information is correct at the time of going to press.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot  European standard and and printing  Due to manufacturing processes we cannot  European standard and minding of Correct as at 15 October 2018 0823  and dimensions without prior notice.  | Plate Finish                                     | Linea-Duo CFX Bright Chrome Frame/Bright Steel                   |  |
| Dimensions (Nominal)  Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Switched Poles  N/A  IP Rating  IP2XD  Contact Gap Minimum  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Business Resource and Mark No 2398667  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Business Resource All Products Recommended Under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Business Resource All Products at 15 October 2018 R83  Business Resource All Products at 15 October 2018 R83  Business Resource All Products at 15 October 2018 R83  Business Resource All Products at 15 October 2018 R83  Business Resource Resource All Products at 15 October 2018 R83  Business Resource Resource Resource Resource Resource Resource Reserve Resource Resou | Insert Colour                                    | Black  |  |
| Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  N/A  IP Rating  IP Rating | EAN13 Barcode                                    | 5017504201685  |  |
| Minimum Wall Box Depth 35mm  Switched Poles N/A  IP Rating IP2XD  Contact Gap Minimum N/A  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed (ref BS7671 415.2.1)  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited apparent spatem.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and officentions without prior notice.  BUstomanade and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:25   | Dimensions (Nominal)                             | Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm             |  |
| Switched Poles   N/A     IP Rating   IP2XD     Contact Gap Minimum   N/A     Earth Terminal Capacity 1   5 x 1mm2     Earth Terminal Capacity 2   4 x 1.5mm2     Earth Terminal Capacity 3   3 x 2.5mm2     Earth Terminal Capacity 4   1 x 4mm2 Multi-strand     Earth Terminal Capacity 5   1 x 6mm2     Earth Terminal Capacity 5   1 x 6mm2     Earth Terminal Capacity 5   1 x 6mm2     Earth Terminal Capacity 6   1 x 6mm2     Earth Terminal Capacity 5   1 x 6mm2     Product Class 1   Must be earthed (ref BS7671 415.2.1)     Ambient Operating Temperature   -5° to +40°C     Recommended Location   Internal Use Only     Maximum Installation Altitude   2000m     Maximum Installation Altitude   2000m     Linea is a Registered Trade Mark No 2398665     Patents and Trademarks   CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174     All products listed conform to current British or European standard and the product information is correct at the time of going to press.     All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.   The refore, we reserve the right to alter designs and dimensions without prior notice.     BEN ISO 9001 : 2015 Quality Management System.   Therefore, we reserve the right to alter designs and dimensions without prior notice.     BEN ISO 9001 : 2015 Quality Management System.   Therefore, we reserve the right to alter designs and dimensions without prior notice.     Due to manufacturing processes we cannot guarantee an exact colour match and shadings of   Correct as at 15 October 2018 08:28   | Fixing Hole Centres                              | Box Fixing = 60.3mm Grid Fixing = CFX Clips                      |  |
| IP Rating IP Rating IP Rating IP PXD  Contact Gap Minimum N/A  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed (ref BS7671 415.2.1)  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Maximum Installation Altitude 2000m  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No, GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of   | Minimum Wall Box Depth                           | 35mm   |  |
| Contact Gap Minimum  N/A  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Must be earthed (ref BS7671 415.2.1)  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Every product of the company to improve products as part of our development by the minimations of reproduction and printing guarantee an exact colour match and shadings of  Every product of the company to improve products as a part of our development programme.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  | Switched Poles                                   | N/A  |  |
| Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed (ref BS7671 415.2.1)  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Maximum Installation Altitude 2000m  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Expression of the company to improve products and dimensions without prior notice.   | IP Rating  | IP2XD  |  |
| Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  2000m  Maximum Installation Altitude  2000m  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Blustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 08:23  | Contact Gap Minimum                              | N/A  |  |
| Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Patents and Trademarks  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Bllustrations and diagrams are reproduced within the limitations of reproduction and printing  Barth Terminal Capacity 4  1 x 4mm2 Multi-strand  1 x 6mm2  Must be earthed (ref BS7671 415.2.1)  Australia Search (ref BS7671 415.2.1)  Linea Green  1 x 6mm2  Linea Green  Linea Green  1 x 6mm2  Linea Green  Linea Green  2 x 4mm2 Multi-strand  2 x 6mm2  Linea Green  Line | Earth Terminal Capacity 1                        | 5 x 1mm2   |  |
| Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  But to manufacturing processes we cannot the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Example 1 x 4mm2 Multi-strand  1 x 4 | Earth Terminal Capacity 2                        | 4 x 1.5mm2   |  |
| Earth Terminal Capacity 5  Product Class 1  Must be earthed (ref BS7671 415.2.1)  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 08:23   | Earth Terminal Capacity 3                        | 3 x 2.5mm2   |  |
| Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 08:23  | Earth Terminal Capacity 4                        | 1 x 4mm2 Multi-strand  |  |
| Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or  European standard and the product information is  correct at the time of going to press.  All accessories are manufactured under an accredited  BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 08:23  | Earth Terminal Capacity 5                        | 1 x 6mm2   |  |
| Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or  European standard and the product information is  correct at the time of going to press.  All accessories are manufactured under an accredited  BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 08:23   | Product Class 1                                  | Must be earthed (ref BS7671 415.2.1)                             |  |
| Maximum Installation Altitude  2000m  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 08:23  Correct as at 15 October 2018 08:23  | Ambient Operating Temperature                    | -5° to +40°C   |  |
| Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 08:23   | Recommended Location                             | Internal Use Only  |  |
| Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 08:23  | Maximum Installation Altitude                    | 2000m  |  |
| European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of  | Patents and Trademarks                           | CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B |  |
| the limitations of reproduction and printing guarantee an exact colour match and shadings of   | European standard and the product information is |  | as part of our development programme. Therefore, we reserve the right to alter designs |
|  | the limitations of reproduction and printing     | guarantee an exact colour match and shadings of                  | Correct as at 15 October 2018 08:23 AM<br>E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











