SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


LDTVSATSB-SSB

Linea-Duo CFX Satin Brass Frame/Satin Steel Front 2 gang Non-Isolated TV+Satellite 2in/2out Black


Item Image







Dimensions



Primary Range Linea-Duo CFX Insert Type 2 gang Non-Isolated TV+Satellite 2in/2out Plate Finish Linea-Duo CFX Satin Brass Frame/Satin Steel Insert Colour Black EAN13 Barcode 5017504161682 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Insert Type Plate Finish Insert Colour EAN13 Barcode Dimensions (Nominal) Fixing Hole Centres	2 gang Non-Isolated TV+Satellite 2in/2out Linea-Duo CFX Satin Brass Frame/Satin Steel Black 5017504161682		
Plate Finish Linea-Duo CFX Satin Brass Frame/Satin Steel Insert Colour Black EAN13 Barcode 5017504161682 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Plate Finish Insert Colour EAN13 Barcode Dimensions (Nominal) Fixing Hole Centres	Linea-Duo CFX Satin Brass Frame/Satin Steel Black 5017504161682		
Insert Colour	Insert Colour EAN13 Barcode Dimensions (Nominal) Fixing Hole Centres	Black 5017504161682		
EAN13 Barcode 5017504161682 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	EAN13 Barcode Dimensions (Nominal) Fixing Hole Centres	5017504161682		
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Dimensions (Nominal) Fixing Hole Centres			
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx 4mm2 Multi-strand Earth Terminal Capacity 5 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Fixing Hole Centres	Cingle: Height OC Own Width OC Own Donth 4 Own	5017504161682	
Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)		Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm		
Switched Poles IP Rating IP Rating IP Rating IP Rating IP Rating N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 I x 4mm2 Multi-strand Earth Terminal Capacity 5 Product Class 1 Must be earthed (ref BS7671 415.2.1)	T	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
IP Rating Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx 4mm2 Multi-strand Earth Terminal Capacity 5 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Minimum Wall Box Depth	35mm		
Contact Gap Minimum Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx 4mm2 Multi-strand Earth Terminal Capacity 5 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Switched Poles	N/A		
Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	IP Rating	IP2XD		
Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Contact Gap Minimum	N/A		
Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1)	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Must be earthed (ref BS7671 415.2.1)	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
	Earth Terminal Capacity 5	1 x 6mm2		
	Product Class 1	Must be earthed (ref BS7671 415.2.1)		
Ambient Operating Temperature -5° to +40°C	Ambient Operating Temperature	-5° to +40°C		
Recommended Location Internal Use Only	Recommended Location	Internal Use Only		
Maximum Installation Altitude 2000m	Maximum Installation Altitude	2000m		
Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice.	European standard and the product information is		Therefore, we reserve the right to alter designs	
Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.		guarantee an exact colour match and shadings of	Correct as at 15 October 2018 08:24 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)17179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84











