SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


LDTVSATSB-SSW

Linea-Duo CFX Satin Brass Frame/Satin Steel Front 2 gang Non-Isolated TV+Satellite 2in/2out White

Item Image







Dimensions




Plate Finish Linea-Duo CFX Satin Brass Frame/Satin Steel Insert Colour White EAN13 Barcode 5017504160685 Solimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Minimum Wall Box Depth 35mm Minimum Wall Box Depth 37mm Minimum Wall Box Depth 37mm Minimum Wall Box Depth 38mm Minimum Wall Box Depth 38mm Minimum Wall Box Depth 39mm Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 A x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ambient Operating Temperature Froduct Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature Maximum Installation Altitude Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product Information is correct at the time of going to press. It is the policy of the company to improve products a part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice.	Primary Range	Linea-Duo CFX	
Insert Colour White EAN13 Barcode 5017504160685 Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 4-5" to +40"C Recommended Location Maximum Installation Altitude Patents and Trademarks All products listed conform to current British or European standard and the product Information is correct at the time of going to press. Bush So 9001: 2015 Quality Management System. Due to manufacting processes we cannot Correct as at 15 October 2018 824 guarantee an exact colour match ashadings of	Insert Type	2 gang Non-Isolated TV+Satellite 2in/2out	
EAN13 Barcode Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles IP2XD Contact Gap Minimum N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude Patents and Trademarks Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. Business Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No. R21 = 3021173 SS2 = 3021174 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. Business Registered Trade Mark No 2398667 European standard and the product information is correct at the time of going to press. Due to manufacturing processes we cannot under an excredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. Experimental Capacity Associated and the product information is guarantee an exact colour mark and shadings of EX	Plate Finish	Linea-Duo CFX Satin Brass Frame/Satin Steel	
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum NA Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Patents and Trademarks Linea is a Registered Trade Mark No 2398667 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Business Registered Trade Mark No 2398667 All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Therefore, we reserve the right to atter designs and dimensions without prior notice. Business Registered Trade Mark No 2398667 Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 Lis the policy of the company to improve products as pan of our development programme. Therefore, we reserve the right to atter designs and dimensions without prior notice. Expression of the production and printing augurantee an exact colour match and shadings of Correct as at 15 October 2018 80.24 Expression of the company to improve products and dimensions without prior notice.	Insert Colour	White	
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm N/A IP Rating IP Rating	EAN13 Barcode	5017504160685	
Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BS EN ISO 9001 : 2015 Quality Management System. Correct as at 15 October 2018 08.24 E8	Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm	
Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Linea is a Registered Trade Mark No 2398665 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited It is the policy of the company to improve products All accessories are manufactured under an accredited It is the policy of the company to improve products All accessories are manufactured under an accredited It is the policy of the company to improve products All accessories are manufactured under an accredited It is the policy of the company to improve products All accessories are manufactured under an accredited It is the policy of the company to improve products All accessories are manufactured under an accredited It is the policy of the company to improve products All accessories are manufactured under an accredited It is the policy of the company to improve products All accessories are manufactured under an accredited It is the policy of the company to improve products All accessories are manufactured under an accredited It is the policy of the company to improve products All accessories are manufactured under an accredited It is the policy of the company to improve products All accessories are manufactured under an accredited It is the policy of the company to improve products All	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:24	Minimum Wall Box Depth	35mm	
Contact Gap Minimum Rarth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Bue to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:24 Earth Terminal Capacity 2 4 x 1.5mm2 1 x 4mm2 Multi-straton 1 x 6mm2 Must be earthed (ref BS7671 415.2.1) All product Class 1 Must be earthed (ref BS7671 415.2.1) Internal Use Only Earth Terminal Capacity 3 1 x 4mm2 Multi-straton Internal Use Only Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-straton Internal Use Only Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capa	Switched Poles	N/A	
Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E8	IP Rating	IP2XD	
Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude 2000m Maximum Installation Altitude Patents and Trademarks Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. Illustrations and diagrams are reproducted within the limitations of reproduction and printing Put Maximum Installation Altitude All products listed conform to current British or European standard and the product information is correct at the time of going to press. Blustrations and diagrams are reproducted within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:24 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand 1 x 4mm2 Multi-strand 1 x 4mm2 Multi-strand 1 x 4mm2 Multi-strand 2 x 4 x 1.5mm2 1 x 4mm2 Multi-strand 2 x 4 x 1.5mm2 2 x 4 x 1.5mm2 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand 2 x 4 x 1.5mm2 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 4mm2 Multi-strand 2 x 4 x 1.5mm2 2 x 4 x 1.5mm2 4 x 4 x 1.5mm2 2 x 4 x 1.5mm2 4 x 4 x 1.5mm2 2 x 4 x 1.5mm2 2 x 4 x 1.5mm2 3 x 2.5mm2 4 x 4 x 1.5mm2 4 x 4 mm2 Multi-strand 5 x 6 x 4 x 1.5mm2 2 x 6 x 4 x 1.5mm2 4 x 1.5mm2 2 x 6 x 4 x 1.5mm2 4 x 1.5mm2 2 x 6 x 4 x 1.5mm2 4 x 1.5mm2 2 x 6 x 4 x 1.5mm2 5 x 6 x 4 x 1.5mm2 4 x 1.5mm2 5 x 6 x 4 x 1.5mm2 6 x 7 x 6 x 7 x 1 x 1 x 1 x 1 x 1 x 1 x 1 x 1 x 1	Contact Gap Minimum	N/A	
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude Patents and Trademarks Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing Barth Terminal Capacity 4 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed (ref BS7671 415.2.1) All so be arrhed (ref BS7671 415.2.1) All so Correct at the time of going to press. Barth Terminal Capacity 4 1 x 4mm2 Multi-strand 1 x 6mm2 Product Class 1 Linea Safety Capacity All Safety Capacity Capacity All Safety Capacity All Safety Capacity	Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All listrations and diagrams are reproduced within the limitations of reproduction and printing Purpose A service of the American Science of the service	Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 5 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:24 E8	Earth Terminal Capacity 3	3 x 2.5mm2	
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conforms to current British or European standard and the product information is correct at the time of going to press. Blustrations and diagrams are reproduced within the limitations of reproduction and printing Must be earthed (ref BS7671 415.2.1) All occurrent BS7671 415.2.1) Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:24	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:24	Earth Terminal Capacity 5	1 x 6mm2	
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:24	Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Maximum Installation Altitude 2000m Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:24	Ambient Operating Temperature	-5° to +40°C	
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:24 E8	Recommended Location	Internal Use Only	
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:24	Maximum Installation Altitude	2000m	
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:24	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B	
the limitations of reproduction and printing guarantee an exact colour match and shadings of E8	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 15 October 2018 08:24 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











