Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sr	mart Lighting Control & Multi-room Audio
		a a a a a a a a a a a a a a a a a a a
LDUS2PB-SSW		
Linea-Duo CFX Polished Brass Frame/Satin Steel Front 1 gang 2A Unswitched Socket White		
Item Image	Wiring	Dimensions
	Neutral Live	Hemilton LINEA DUO CFX US2 Unswitched Socket
Primary Range	Linea-Duo CFX	
Insert Type	1 gang 2A Unswitched Socket	
Plate Finish	Linea-Duo CFX Polished Brass Frame/Satin Steel	
Insert Colour	White	
EAN13 Barcode	5017504140045	
	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm	
Dimensions (Nominal)		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	None	
Current Rating	2 Amp	
Voltage	220/250V AC	
Maximum Load	2 Amp	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	None	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	2 x 2.5mm2	
Terminal Capacity 4	1 x 4mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	2 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 546	
Additional Notes	Shuttered: Yes	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:24 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F T: +44 (0)1747 860088 F: +44 (0)179 710414 E: info@hamilton-litestat.com Registered	toad, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB n London No. 941624 VAT Registration No. 222 6607 84	Listed in STrimble product selector

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio