making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDUS5PB-BSW

Linea-Duo CFX Polished Brass Frame/Bright Steel Front 1 gang 5A Unswitched Socket White


Item Image



Wiring



Dimensions



Primary Range	Linea-Duo CFX		
Insert Type	1 gang 5A Unswitched Socket		
Plate Finish	Linea-Duo CFX Polished Brass Frame/Bright Steel		
Insert Colour	White		
EAN13 Barcode	5017504130053	5017504130053	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Switched Poles	None		
Current Rating	5 Amp		
Voltage	220/250V AC		
Maximum Load	5 Amp		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	None		
Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 3	2 x 2.5mm2		
Terminal Capacity 4	1 x 4mm2		
Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	2 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2		
Product Class 1	Must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS 546		
Additional Notes	Shuttered: Yes		
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within	Due to manufacturing processes we cannot	Correct as at 15 October 2018 08:24 AM	

guarantee an exact colour match and shadings of

of certain finishes.

process and are not binding. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

the limitations of reproduction and printing











E&OE





Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio