Hamilton

making connections beautifully

SL

| | Wiring Accessories • Circuit Protection • Sr | nart Lighting Control & Multi-room Audio | | |
|---|---|---|--|--|
| | LGX1X40PB-SB | hard Egnang Control & Flater ContrAddio | | |
| Linea-Georgian CFX Polished Brass Frame/Satin Brass Front 1x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Polished Brass | | | | |
| Item Image | Wiring | Dimensions | | |
| | Drumer Weing | EXAMPLE A GEORGIAN CFX 1X40 Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer | | |
| Primary Range | Linea-Georgian CFX | | | |
| Insert Type | 1 gang 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer | | | |
| Plate Finish | Linea-Georgian CFX Polished Brass Frame/Satin Brass | | | |
| Insert Colour | Polished Brass | | | |
| EAN13 Barcode | 5017504819415 | | | |
| Dimensions (Nominal) | Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm | | | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | | | |
| Minimum Wall Box Depth | 35mm | | | |
| Wattage | 400W | | | |
| Switched Poles | Single | | | |
| Current Rating | 1.66 Amp | | | |
| Voltage | 220/250V AC | | | |
| Maximum Load | 400W resistive Min Load | | | |
| Mains Frequency | 50Hz | | | |
| IP Rating | IP2XD | | | |
| Contact Gap Minimum | N/A | | | |
| Terminal Capacity 1 | 2 x 1mm2 | | | |
| Terminal Capacity 2 | 2 x 1.5mm2 | | | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | | | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | | | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | | | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | | | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | | | |
| Product Class 1 | Face plate must be earthed | | | |
| Ambient Operating Temperature | -5° to +40°C | | | |
| Recommended Location | Internal Use Only | | | |
| Maximum Installation Altitude | 2000m | | | |
| Standard/Approval | BS EN 60669-2-1 | | | |
| Additional Notes | Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. | | | |

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LGX1X40PB-SB

Linea-Georgian CFX Polished Brass Frame/Satin Brass Front 1x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Polished Brass

| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. G Linea-Georgian CFX is a UK Registered Design Certificate | |
|---|---|--|
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:03 AM E&OE |
| | A, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondron No. 9416/24 VAT Registration No. 222 6607 84 | Listed in Strimble product product Sector String Contraction String Co |

SL