Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio
LGX2J12CB-CBB		
Linea-Georgian CFX Copper Bronze Frame/Copper Bronze Front 2 gang RJ12 Outlet - Unshielded Black		
Item Image	Wiring	Dimensions
	Datacom Module Rear View RJ11 / 12 Socket Rear View Cable tile Cable tile	ELEAGE GEORGAL AS A CARACTERISTIC A CARACTERISTICA A CARA
Primary Range	Linea-Georgian CFX	
Insert Type	2 gang RJ12 Outlet - Unshielded	
Plate Finish	Linea-Georgian CFX Copper Bronze Frame/Copper Bronze	
Insert Colour	Black	
EAN13 Barcode	5017504043100	
Dimensions (Nominal)	Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
	5 x 1mm2	
Earth Terminal Capacity 1	4 x 1.5mm2	
Earth Terminal Capacity 2	4 x 1.5mm2 3 x 2.5mm2	
Earth Terminal Capacity 3	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 4		
Earth Terminal Capacity 5	1 x 6mm2 Must be earthed (ref PS7671.415.2.1)	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:04 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville I T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered	Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84	Listed in STrimble Product Selector Disspite Cat Ho Intil128

SL