SL



making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LGX2XLEDITB100PB-SB

Linea-Georgian CFX Polished Brass Frame/Satin Brass 2g 100W LED 2 Way Push On/Off Rotary Dimmer Polished Brass

Item Image Wiring **Dimensions** Hamilton 2XLEDITB
LEDITB100 2 Way Dimme Primary Range Linea-Georgian CFX Insert Type 2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Linea-Georgian CFX Polished Brass Frame/Satin Brass Insert Colour Polished Brass EAN13 Barcode 5017504083434 Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang 50Hz Mains Frequency IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm² Product Class 1 Face plate muct be earthed -5°C to +40°C **Ambient Operating Temperature** Internal Use Only Recommended Location Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001: 2015 Quality Management System as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 15 October 2018 09:04 AM the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

F: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









