



LGX3X40EB-EB

Linea-Georgian CFX Etrium Bronze Frame/Etrium Bronze Front 3x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers Etrium Bronze

Item Image	Wiring	Dimensions
 <p>Hamilton LINEA GEORGIAN CFX 3X40 Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer</p> <p>Dimensions: 154.5mm width, 95.5mm height, 4.0mm depth.</p>	 <p>Dimmer Wiring: Line, Neutral, Lamp.</p> <p>Loop In Loop Out Two Way Switching: Line, Neutral, Lamp.</p> <p>Note: When using as a 2-Way Dimmer the L2 terminal is not used.</p> <p>Note: When switching from more than one position a two-way dimmer can only be used in conjunction with switches, i.e. only one dimmer per circuit.</p>	<p>Primary Range</p> <p>Insert Type</p> <p>Plate Finish</p> <p>Insert Colour</p> <p>EAN13 Barcode</p> <p>Dimensions (Nominal)</p> <p>Fixing Hole Centres</p> <p>Minimum Wall Box Depth</p> <p>Wattage</p> <p>Switched Poles</p> <p>Current Rating</p> <p>Voltage</p> <p>Maximum Load</p> <p>Mains Frequency</p> <p>IP Rating</p> <p>Contact Gap Minimum</p> <p>Terminal Capacity 1</p> <p>Terminal Capacity 2</p> <p>Earth Terminal Capacity 1</p> <p>Earth Terminal Capacity 2</p> <p>Earth Terminal Capacity 3</p> <p>Earth Terminal Capacity 4</p> <p>Earth Terminal Capacity 5</p> <p>Product Class 1</p> <p>Ambient Operating Temperature</p> <p>Recommended Location</p> <p>Maximum Installation Altitude</p> <p>Standard/Approval</p> <p>Additional Notes</p>
Primary Range	Linea-Georgian CFX	
Insert Type	3 gang 400w Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer	
Plate Finish	Linea-Georgian CFX Etrium Bronze Frame/Etrium Bronze	
Insert Colour	Etrium Bronze	
EAN13 Barcode	5017504043445	
Dimensions (Nominal)	Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Wattage	400W per gang	
Switched Poles	Single	
Current Rating	1.66 Amps per gang	
Voltage	220/250V AC	
Maximum Load	400W resistive per gang	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Terminal Capacity 1	2 x 1mm ²	
Terminal Capacity 2	2 x 1.5mm ²	
Earth Terminal Capacity 1	5 x 1mm ²	
Earth Terminal Capacity 2	4 x 1.5mm ²	
Earth Terminal Capacity 3	3 x 2.5mm ²	
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand	
Earth Terminal Capacity 5	1 x 6mm ²	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-2-1	
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.	

LGX3X40EB-EB

Linea-Georgian CFX Etrium Bronze Frame/Etrium Bronze Front 3x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers Etrium Bronze

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at 15 October 2018 09:04 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414

E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM11238