Hamilton

making connections beautifully

SL

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio			
LGX3X40HB-HB			
Linea-Georgian CFX Connaught Bronze Frame/Connaught Bronze Front 3x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers Connaught Bronze			
Item Image	Wiring	Dimensions	
	Dimmer Weing The Narray The	ELECTRIC LA CONCUENCIA CALANA BESISTIVE LA CAGUA CALANA 2 Way Switching Dimmer 144 145 145 145 145 145 145 145	
Primary Range	Linea-Georgian CFX		
Insert Type	3 gang 400w Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer		
Plate Finish	Linea-Georgian CFX Connaught Bronze Frame/Connaught Bronze		
Insert Colour	Connaught Bronze		
EAN13 Barcode	5017504043452		
Dimensions (Nominal)	Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Wattage	400W per gang		
Switched Poles	Single		
Current Rating	1.66 Amps per gang		
Voltage	220/250V AC		
Maximum Load	400W resistive per gang		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	N/A		
Terminal Capacity 1	2 x 1mm2		
Terminal Capacity 2	2 x 1.5mm2		
Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Face plate must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1		
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.		

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LGX3X40HB-HB

Linea-Georgian CFX Connaught Bronze Frame/Connaught Bronze Front 3x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers Connaught Bronze

	, , , , , , , , , , , , , , , , , , , ,	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accr BS EN ISO 9001 : 2015 Quality Management Sy	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we canno guarantee an exact colour match and shading of certain finishes.	
	ad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ordon No. 941624 VAT Registration No. 222 6607 84	COMPRESAN SOCIAL

SL