

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **LGX3XTSAB-ABB**

| Linea-Georgian CFX Antique Brass Frame/Antique Brass Front 3 gang Multi-Way Touch Slave Controller Antique Brass/Black |   |   |  |  |
|--|---|---|--|--|
| Item Image   | Wiring  | Dimensions  |  |  |
|  | Multi-Way Wiring using Slave module(s)  Multi-Way Wiring using Slave module(s)  Lis s Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q   | LINEA GEORGIAN CFX 3XTS Multi-WayTouch Slave Controller |  |  |
| Primary Range  | Linea-Georgian CFX  |   |  |  |
| Insert Type  | 3 gang Multi-Way Touch Slave Controller   |   |  |  |
| Plate Finish   | Linea-Georgian CFX Antique Brass Frame/Antique Brass  |   |  |  |
| Insert Colour  | Antique Brass/Black   |   |  |  |
| EAN13 Barcode  | 5017504791599   |   |  |  |
| Dimensions (Nominal)   | Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm   |   |  |  |
| Fixing Hole Centres  | Box Fixing = 120.6mm Grid Fixing = CFX Clips  |   |  |  |
| Minimum Wall Box Depth   | 35mm  |   |  |  |
| Wattage  | The same as Touch Master or Ceiling Dimmer  |   |  |  |
| Switched Poles   | N/A   |   |  |  |
| Current Rating   | The same as Touch Master or Ceiling Dimmer  |   |  |  |
| Voltage  | 220/250V AC   |   |  |  |
| Maximum Load   | The same as Touch Master  |   |  |  |
| Mains Frequency  | 50Hz  |   |  |  |
| IP Rating  | IP2XD   |   |  |  |
| Contact Gap Minimum  | N/A   |   |  |  |
| Terminal Capacity 1  | 2 x 1mm2  |   |  |  |
| Terminal Capacity 2  | 2 x 1.5mm2  |   |  |  |
| Earth Terminal Capacity 1  | 5 x 1mm2  |   |  |  |
| Earth Terminal Capacity 2  | 4 x 1.5mm2  |   |  |  |
| Earth Terminal Capacity 3  | 3 x 2.5mm2  |   |  |  |
| Earth Terminal Capacity 4  | 1 x 4mm2 Multi-strand   |   |  |  |
| Earth Terminal Capacity 5  | 1 x 6mm2  |   |  |  |
| Product Class 1  | Face plate must be earthed  |   |  |  |
| Ambient Operating Temperature  | -5° to +40°C  |   |  |  |
| Recommended Location   | Internal Use Only   |   |  |  |
| Maximum Installation Altitude  | 2000m   |   |  |  |
| Standard/Approval  | BS EN 60669-2-1   |   |  |  |
| Additional Notes   | Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers |   |  |  |



SL

making connections beautifully

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio   |   |  |  |
|---|---|--|--|
| LGX3XTSAB-ABB   |   |  |  |
| Linea-Georgian CFX Antique Brass Frame/Antique Brass Front 3 gang Multi-Way Touch Slave Controller Antique Brass/Black                          |   |  |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 |  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |  |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing   | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  | Correct as at 15 October 2018 09:04 AM<br>E&OE   |  |

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











