Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio LGX45NHB-HBB Linea-Georgian CFX Connaught Bronze Frame/Connaught Bronze Front 1 gang 45A Double Pole Rocker and Neon Red/Black Item Image Wiring Dimensions Hamilton 45N Double Pole Red Rocker & Neon Primary Range Linea-Georgian CFX Insert Type 1 gang 45A Double Pole Red Rocker + Neon Plate Finish Linea-Georgian CFX Connaught Bronze Frame/Connaught Bronze Insert Colour Red/Black EAN13 Barcode 5017504043681 Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 45 Amp 220/250V AC Voltage Maximum Load 45 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm **Terminal Capacity 1** 3 x 6mm2 **Terminal Capacity 2** 2 x 10mm2 **Terminal Capacity 3** 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Internal Use Only Recommended Location Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 15 October 2018 09:04 AM the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE of certain finishes. process and are not binding. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ SECA T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 LUCKINS

SL