Hamilton

making connections beautifully

SL

	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio		
LGX4X40PB-AB Linea-Georgian CFX Polished Brass Frame/Antique Brass Front 4x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers max 300W per gang Polished Brass				
	Drumer-Woring Line Touring The Strateging The Strateging T	Electric Construction of the second s		
Primary Range	Linea-Georgian CFX			
Insert Type	4 gang 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer max 300W per gang			
Plate Finish	Linea-Georgian CFX Polished Brass Frame/Antique Brass			
Insert Colour	Polished Brass			
EAN13 Barcode	5017504829445			
Dimensions (Nominal)	Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm			
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips			
Minimum Wall Box Depth	35mm			
Wattage	300W per gang			
Switched Poles	Single			
Current Rating	1.25 Amps per gang			
Voltage	220/250V AC			
Maximum Load	300W resistive per gang			
Mains Frequency	50Hz			
IP Rating	IP2XD			
Contact Gap Minimum	N/A			
Terminal Capacity 1	2 x 1mm2			
Terminal Capacity 2	2 x 1.5mm2			
Earth Terminal Capacity 1	5 x 1mm2			
Earth Terminal Capacity 2	4 x 1.5mm2			
Earth Terminal Capacity 3	3 x 2.5mm2			
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand			
Earth Terminal Capacity 5	1 x 6mm2			
Product Class 1	Face plate must be earthed			
Ambient Operating Temperature	-5° to +40°C			
Recommended Location	Internal Use Only			
Maximum Installation Altitude	2000m			
Standard/Approval	BS EN 60669-2-1			
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse b should be de-rated by 25%. When dimming LED lamps de-ra	base. When using mains voltagehalogen lamps- dimmers ted by 75% - please contact our Technical for compatibility.		

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LGX4X40PB-AB

Linea-Georgian CFX Polished Brass Frame/Antique Brass Front 4x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers max 300W per gang Polished Brass

	5 1 5 5	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:05 AM E&OE
	ad, Brislington, Bristol, BS4 5NZ fice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in STrimble Product Selector DSSPlus (COLD Selector Selector CELLER MI128)

SL