SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio **LGXDTVMCB-CBB** Linea-Georgian CFX Copper Bronze Frame/Copper Bronze Front 1 gang Non-Isolated TV (Male) Black Item Image Wiring **Dimensions** Hamilton DTVM Non-Isolated TV (male) EMC Gasket Conductor Terminal Screw Correct position of conductor, screening braid and cable Primary Range Linea-Georgian CFX Insert Type 1 gang Non-Isolated TV (Male) (DAB Compatible) Plate Finish Linea-Georgian CFX Copper Bronze Frame/Copper Bronze Insert Colour Black EAN13 Barcode 5017504045227 Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Must be earthed (ref BS7671 415.2.1) Product Class 1 -5° to +40°C **Ambient Operating Temperature** Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet Frequencies 1 FM DC=5-2200 MHz Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 09:06 AM Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

process and are not binding.











