SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

**LGXDTVMEB-EBB** Linea-Georgian CFX Etrium Bronze Frame/Etrium Bronze Front 1 gang Non-Isolated TV (Male) Black Item Image Wiring **Dimensions** Hamilton DTVM Non-Isolated TV (male) EMC Gasket Conductor Terminal Screw Correct position of conductor, screening braid and cable Primary Range Linea-Georgian CFX Insert Type 1 gang Non-Isolated TV (Male) (DAB Compatible) Plate Finish Linea-Georgian CFX Etrium Bronze Frame/Etrium Bronze Insert Colour Black EAN13 Barcode 5017504045234 Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2

EuroFix Additional Notes TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet Frequencies 1 FM DC=5-2200 MHz Linea is a Registered Trade Mark No 2398665 Patents and Trademarks

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673

All products listed conform to current British or European standard and the product information is correct at the time of going to press.

Earth Terminal Capacity 4

Earth Terminal Capacity 5

**Ambient Operating Temperature** Recommended Location

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Maximum Installation Altitude

Product Class 1

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

It is the policy of the company to improve products as part of our development programme Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding.

1 x 4mm2 Multi-strand

Must be earthed (ref BS7671 415.2.1)

1 x 6mm2

-5° to +40°C

2000m

Internal Use Only

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











Correct as at 15 October 2018 09:06 AM

