SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LGXJ12PB-SBW

Linea-Georgian CFX Polished Brass Frame/Satin Brass Front 1 gang RJ12 Outlet - Unshielded White

| Linea-Georgian CFX Polished Brass Frame/Satin Brass Front 1 gang RJ12 Outlet - Unshielded White   |  |  |
|---|--|--|
| Item Image  | Wiring   | Dimensions   |
| Camaanaanaan kaanaanaanaana   | Datacom Module Rear View  RJ11 / 12 Socket Rear View  Cable tie  anchor  Cable tie  SSELLI / 12 Justice Color Fooder  SSELLI / 12 Justice Colo | Hemiton LINEA GEORGIAN CFX 112 1 gang RJ12 Outlet Unshielded 6 wire  |
| Primary Range   | Linea-Georgian CFX   |  |
| Insert Type   | 1 gang RJ12 Outlet - Unshielded  |  |
| Plate Finish  | Linea-Georgian CFX Polished Brass Frame/Satin Brass  |  |
| Insert Colour   | White  |  |
| EAN13 Barcode   | 5017504810559  |  |
| Dimensions (Nominal)  | Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm   |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |  |
| Minimum Wall Box Depth  | 35mm   |  |
| Switched Poles  | N/A  |  |
| IP Rating   | IP2XD  |  |
| Contact Gap Minimum   | N/A  |  |
| Earth Terminal Capacity 1   | 5 x 1mm2   |  |
| Earth Terminal Capacity 2   | 4 x 1.5mm2   |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2   |  |
| Earth Terminal Capacity 4   | 1 x 4mm2 Multi-strand  |  |
| Earth Terminal Capacity 5   | 1 x 6mm2   |  |
| Product Class 1   | Must be earthed (ref BS7671 415.2.1)   |  |
| Ambient Operating Temperature   | -5° to +40°C   |  |
| Recommended Location  | Internal Use Only  |  |
| Maximum Installation Altitude   | 2000m  |  |
| EuroFix Additional Notes  | Can be used as either RJ11 (4 wires) or RJ12 (6 wires)   |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 15 October 2018 09:06 AM<br>E&OE   |

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











