

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LGXK21CB-CBB

Item Image	Wiring	Dimensions
	Abertraine 2 very sentrang	Hemilton LINEA GEORGIAN CFX K21 2 Way Key switch
nsert Type	1 gang 20AX 2 Way Key Switch	
late Finish	Linea-Georgian CFX Copper Bronze Frame/Copper Bronze	
sert Colour	Black	
AN13 Barcode	5017504045777	
imensions (Nominal)	Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm	
ixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
inimum Wall Box Depth	35mm	
witched Poles	Single	
urrent Rating	20AX	
oltage	220/250V AC	
laximum Load	20 Amp inductive	
lains Frequency	50Hz	
Rating	IP2XD	
ontact Gap Minimum	3mm	
erminal Capacity 1	5 x 1mm2	
erminal Capacity 2	4 x 1.5mm2	
erminal Capacity 3	2 x 2.5mm2	
erminal Capacity 4	2 x 4mm2 Multi-strand	
erminal Capacity 5	1 x 6mm2	
arth Terminal Capacity 1	6 x 1mm2	
arth Terminal Capacity 2	5 x 1.5mm2	
arth Terminal Capacity 3	3 x 2.5mm2	
arth Terminal Capacity 4	2 x 4mm2 Multi-strand	
arth Terminal Capacity 5	1 x 6mm2	
roduct Class 1	Must be earthed	
mbient Operating Temperature	-5° to +40°C	
ecommended Location	Internal Use Only	
laximum Installation Altitude	2000m	
tandard/Approval	BS EN 60669-1	
atents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB Linea-Georgian CFX is a UK Registered Design Certificate No.	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:06 E8

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio