

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LGXR222PB-ABB

the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	Linea-Georgian CFX Polished Brass Frame/Antique Brass Front 2 gang 20AX 2 Way Rocker Polished Brass/Black			
Primary Range Linea-Georgian CFX  Insert Type 2 gang 20X 2 Way Rocker Plate Flaich Unes-Georgian CFX Polished Brass Framil-Antique Brass Insert Colour Polished Brass Flame Antique Brass Insert Colour Brass Brass Flame Antique Brass Insert Colour Brass Brass Flame Antique Brass Insert Colour Brass Brass Brass Flame Antique Brass Insert Brass Brass Brass Brass Brass Flame Antique Brass Insert Brass	Item Image	Wiring	Dimensions	
Insert Type  2 gang 20AX 2 Way Rocker Linea-Georgian CFX Polished Brass Frame/Antique Brass Insert Colour Polished Brass/Black  EAN13 Barcode 5017504822278 Dimensions (Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Fixing Holio Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Simple Witched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP PXD Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 9 1 x 6 x 1.5mm2 Earth Terminal Capacity 9 1 x 6 x 1.5mm2 Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capa		Abtending 2 way switching	R222 2 Way Rocker	
Plate Finish Linear-Georgian CFX Polished Brass Flame/Antique Brass Insert Colour Polished Brass/Black Annual Sarcode Soft7504822378 Dimensions (Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Somm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency FRating IP2XD Context Gap Minimum Som Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 4 x 1.5mm2 Terminal Capacity 4 2 x 4.4mm2 Multi-strand Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5				
Insert Colour		2 gang 20AX 2 Way Rocker		
EAN13 Barcode 5017504822378 Dimensions (Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 220250V AC Waximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 4 mm Multi-strand Terminal Capacity 4 5 x 1.5mm2 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 8 2 x 4mm2 Multi-strand Earth Terminal Capacity 9 8 x 1.5mm2 Earth Terminal Capacity 9 8 x 2.5mm2 Earth Terminal Capacity 9 8 x 1.5mm2 Earth Terminal Capacity 9 8 x 1.5mm2 Earth Terminal Capacity 9 8 x 2.5mm2 Earth Terminal Capacit	Plate Finish	Linea-Georgian CFX Polished Brass Frame/Antique Brass		
Dimensions (Nominal)  Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  Simm  Switched Poles  Single  Current Rating  20AX  Voltage  220256V AC  Maximum Load  20 Amp inductive  Mains Frequency  50Hz  FRating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x tmm2  Terminal Capacity 1  Terminal Capacity 1  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  2 x 4 x 1.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 3  2 x 2.5mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capa	Insert Colour	Polished Brass/Black		
Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Switched Poles  Single  Current Rating  20AX  Voltage  2202560 V AC  Maximum Load  Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 9  Earth Terminal Capacity 9  Earth Terminal Capacity 9  Earth Terminal Capacity 1  Earth Terminal Capacity 5  Ix 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 9  Earth	EAN13 Barcode	5017504822378		
Minimum Wall Box Depth Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 19 Rating 1P2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x 6mm2 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 2 x 4mm2 Multi-strand Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 4 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 7 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9	Dimensions (Nominal)			
Switched Poles  Current Rating  20AX  Voltage  220/250V AC  220/250V AC  Maximum Load  20 Amp inductive  Mains Frequency  IP Rating	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating 20/X Voltage 220/ZSOV AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm IP2XD Contact Gap Minimum 3mm IP3XD Terminal Capacity 1 5 x mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 4.5mm2 Terminal Capacity 4 7 x 4.5mm2 Terminal Capacity 5 1 x 6mm2 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1.5mm2 Earth Terminal Capacity 1 6 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5.5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Standard/Approval BS EN 60689-1 Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian Certificate No. R21 = 2078674 SS2 = 2078673  All products lated conform to current British or European standard and the product information is correct at the time of going to press.  All products lated conform to current British or European standard and the product information is correct at the time of going to press.  All products lated conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited as pant of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  BS EN 150 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  But the initiations of erpoduction and printing quarantee an exact colour match and standards of	Minimum Wall Box Depth	35mm		
Voltage 220/250V AC  Maximum Load 20 Amp inductive  Mains Frequency 50Hz  IP Rating IP Rating IP Rating IP PXD  Contact Gap Minimum 3mm  Terminal Capacity 1 5x 1mm2  Terminal Capacity 2 4x 1.5mm2  Terminal Capacity 3 2x 2.5mm2  Terminal Capacity 3 2x 4.5mm2  Terminal Capacity 4 5x 1.5mm2  Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 5 5 1x 6mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 2 5x 1.5mm2  Earth Terminal Capacity 3 3x 2.5mm2  Earth Terminal Capacity 4 2x 4mm2 Multi-strand  Earth Terminal Capacity 4 5x 1.5mm2  Earth Terminal Capacity 4 2x 4mm2 Multi-strand  Earth Terminal Capacity 4 1x 6mm2  Froduct Class 1 5x 6mm2  Froduct Class 1 5x 6mm2  Ambient Operating Temperature 5-5 to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 6069-1  Linea is a Registered Trade Mark No 2398667  Patents and Trademarks Linea-Georgian CFX is at UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All coessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  EEON Terminal Capacity A 1x 6mm2  All accessories are manufactured under an accredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  EEON Terminal Capacity A 2x 4mm2 Multi-strand Ample of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  EEON Terminal Capacity A 2x 4mm2 Multi-strand Ample of the company to improve products and and dimensions without prior notice.  EEON Terminal Capacity A 2x 4 5mm2 Multi-strand	Switched Poles	Single		
Maximum Load  Mains Frequency  50Hz  IP Rating  IP ZXD  Contact Cap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 5  I x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capaci	Current Rating	20AX		
Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  Ferminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal	Voltage	220/250V AC		
IP Rating IP Pating IP Rating IP Pating IP Rating IP Pating Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth	Maximum Load	20 Amp inductive		
Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  6 x 1mm2  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 6  1 x 6mm2  Earth Terminal Capacity 6  Ea	Mains Frequency	50Hz		
Terminal Capacity 2  Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 1  Terminal Capacity 1  Terminal Capacity 1  Terminal Capacity 2  Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 3  Terminal Capacity 3  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 3  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 6  Terminal	IP Rating	IP2XD		
Terminal Capacity 2  Terminal Capacity 3  Z x 2.5mm2  Terminal Capacity 4  Z x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  To smm2  Earth Terminal Capacity 5  To smm2  Earth Terminal Capacity 4  Earth Terminal Capacity 5  To smm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  To smm2  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 8  Earth Terminal Capacity 9  To smm2  It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to after designs and dimensions without prior notice.  Exort is a smuthard and the product information is correct at the time of going to press.  Exort is a smuthard and shadings of Correct as at 15 October 2018 09.06 AN Exort Exort Individual States and Shadings of Exort Individual States Individual State	Contact Gap Minimum	3mm		
Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09.06 AM E&O		5 x 1mm2		
Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  The standard Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 6069-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN Is 09001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:06.6 A. E&O.	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:06 AM E&CO	Terminal Capacity 3	2 x 2.5mm2		
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Sx 1.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BL is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 9:9:66 AM E&O	Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Must be earthed  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 09:06 AN E&CO	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 6069-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BULD to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:06 AN E&C	Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All states of the product of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  But to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 09:06 AN E&OC	Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 09:06 AN E&O	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BUILUSTRATIONS and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:06 AN E&OC	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 09:06 AN E&OT	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location	Product Class 1	Must be earthed		
Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 09:06 AN E&OF	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or  European standard and the product information is  correct at the time of going to press.  All accessories are manufactured under an accredited  BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 09:06 AN E&OF	Recommended Location	Internal Use Only		
Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 09:06 AN E&O	Maximum Installation Altitude	2000m		
Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 15 October 2018 09:06 AN E&OE	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB		
Illustrations and diagrams are reproduced within  the limitations of reproduction and printing  Due to manufacturing processes we cannot  Correct as at 15 October 2018 09:06 AN  E&OE  E&OE	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ		guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:06 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio