

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LGXR22PB-SBB

Note	Linea-Georgian CFX Polished B	LGXR22PB-SBB rass Frame/Satin Brass Front 2 gang 10AX 2	Way Rocker Polished Brass/Black	
Primary Range Linea-Georgian CFX Insert Type 2 gang 10AX 2 Way Rocker Plate Finish Linea-Georgian CFX Polishard Brass Prame-Satin Brass Insert Colour Polishard Brass/Black EAN13 Barcode 501750412225 Gange Height = 95.5mm Width = 95.5mm Depth = 4.0mm Pinners Hook Centres Box Fining = 60.9mm Grid Fining = GFX Clips Informational Box Depth 25mm Suitched Poles Current Rating 10AX Current Rating 10AX Current Rating 10AX Current Rating 10AX Contract Gap Mainimum 10AX Single Height = 95.5mm Middle Height = 95.5mm Depth = 4.0mm Pinners Hook Depth 25mm Suitched Poles Current Rating 10AX Current Rating 10AX Tombrial Capacity 3 10AX Tombrial Capacity 4 10AX 10AX 10AX 10AX 10AX 10AX 10AX 10AX				
Insert Type    2 gang 10AX 2 Way Rocker		Alternative 2 way evertaining	R22 2 Way Rocker	
Plate Finish Linear-Colour Polished Brass Frame/Satin Brass Insert Colour Polished Brass Plack EAN13 Barcode Sof17504812225 Dimensions (Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency Softz Paraling Parabo Contact Gap Minimum 3mm Ferminal Capacity 1 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Terminal Capacity 6 1 x 6mm2 Terminal Capacity 6 1 x 6mm2 Terminal Capacity 6 1 x 6mm2 Terminal Capacity 7 Terminal Capacity 8 1 x 6mm2 Terminal Capacity 8 1 x 6mm2 Terminal Capacity 9 Terminal Ca	Primary Range	Linea-Georgian CFX		
Insert Colour  EANT3 Barcode  50175048172225 Dimensions (Nominal)  Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth  25mm  Switched Poles  Single  Current Rating  10AX  Voltage  2200250V AC  Maximum Load  10 Amp inductive  Maxims Frequency  50Hz  IP Rating  IP EXD  Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Fortune Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Fortune Capacity 5  1 x 6mm2  Fortune Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  1 x 4 x 1.5mm2  Earth Terminal Capacity 9  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Fortune Class 1  Must be earthed  Ambient Operating Temperature  1 x 4 mm2 Multi-strand  Earth Terminal Capacity 6  Fortune Class 1  Must be earthed  Must be earthed  Ambient Operating Temperature  1 x 6mm2  Fortune Class 1  Must be earthed  Earth Terminal Capacity 5  1 x 6mm2  Fortune Class 1  Must be earthed  Earth Terminal Capacity 6  Fortune Class 1  Earth Terminal Capacity 6  Fortune Class 1  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Fortune Capacity 6  Earth Terminal Capacity 6  Fortune Capacity 7  Earth Terminal Capacity 6  Earth Te	Insert Type			
EAN13 Barcode    So17504812225   Dimensions (Nominal)   Single: Height = 9.5.mm   Width = 95.5mm   Depth = 4.0mm	Plate Finish	Linea-Georgian CFX Polished Brass Frame/Satin Brass		
Dimensions (Nominal)  Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  Single  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  50Hz  1P Rating  Prating  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 3  1 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 6  Earth Terminal	Insert Colour	Polished Brass/Black		
Fixing Hole Centres   Box Fixing = 60.3mm   Grid Fixing = CFX Clips	EAN13 Barcode	5017504812225		
Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz P Rating P Rating P Rating P Rating P Rating Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 5 x 1mm2 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capac	Dimensions (Nominal)	Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm		
Switched Poles  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 3  1 x 4 mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  1 x 6mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 9  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Term	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating 10AX  Voltage 220/250V AC  Maximum Load 10 Amp inductive  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Smm  Ferminal Capacity 1 5 x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Forduct Class 1 1 x 4mm2 Multi-strand  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 5 1 x 6mm2  Forduct Class 1 Must be earthed  Ambient Operating Temperature 5-5* to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Lines is a Registered Trade Mark No 2398665  Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Lines-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of gloging to press.  All products listed conform to current British or European standard and the product information is correct at the time of gloging to press.  All products listed conform to current British or European standard and the product information is correct at the time of gloging to press.  BEN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to aller designs and dimensions without prior notice.  European standard and the product information is correct at the time of gloging to press.	Minimum Wall Box Depth	25mm		
Voltage 220/250V AC  Maximum Load 10 Amp inductive  Mains Frequency 50Hz  IP Rating IP2XD  Contact Cap Minimum 3mm  Terminal Capacity 1 5 x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 8 1 x 6mm2  Earth Terminal Capacity 9 1 x 4 mm2 Multi-strand  Earth Terminal Capacity 9 1 x 6mm2  Froduct Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  BEN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot Correct as at 15 Cotober 2018 09/07  Linear-Georgian CFX is a 1 W Registered Pracefuled Mark No 2398667  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within	Switched Poles			
Maximum Load  Mains Frequency  50Hz  IP Rating  IP Rati	Current Rating			
Maximum Load  10 Amp inductive  Mains Frequency  50Hz  IP Rating	Voltage			
Mains Frequency  50Hz  IP Rating  IP ZXD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1 mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1 mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  1 x 4mm2 Multi-strand  Earth Terminal Capacity 3  Earth Terminal Capacity 3  In x 6mm2  Earth Terminal Capacity 4  In x 4mm2 Multi-strand  Earth Terminal Capacity 5  In x 6mm2  Froduct Class 1  Must be earthed  Ambient Operating Temperature  5° to x40°C  Recommended Location  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Furches as 15 Colober 2018 99.07  Corct as at 15 Colober 2018 99.07				
IP Rating	Mains Frequency			
Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  It x 6mm2  Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398665 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398665 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398665 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398665 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398665 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398665 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398665 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398665 Patent No. GB 2383375B  Linea is a Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited  BS EN ISO 9001 : 2015 Quality Management System.  But the policy of the company to improve products as part of our development programme. Therefore, we reserve the night to alter designs and dimensions without prior notice.  But the policy of the company to improve products as part of our development programme. Therefore, we reserve the night to alter des				
Terminal Capacity 2  Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 1  Terminal Capacity 6  Terminal Capacity 7  Terminal Capacity 7  Terminal Capacity 7  Terminal Capacity 9  Terminal		3mm		
Terminal Capacity 2  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Froduct Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Under the product information is correct at the time of going to press.  Due to manufacturing processes we cannot  Correct as at 15 October 2018 09:07				
Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 5  In x 4mm2 Multi-strand  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  So to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  European standard and the product information is correct at the time of going to press.  European standard and the product information is correct at the time of going to press.  European standard and the product information is correct at the time of going to press.  European standard and the product information is correct at the time of going to press.  European standard and the product information is correct at the time of going to press.  European standard and the product information is correct at the time of going to press.  European standard and the product information is correct at the time of going to press.  European standard and the product information is correct at the time of going to press.  European standard and the product information is correct at the time of going to press.				
Terminal Capacity 4				
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 8  Earth Terminal Capacity 9				
Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Standard/Approval  BS EN 6069-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  BIUstrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as 1 to Ctober 2018 09:07  Correct as 1 to Correct as 1 to Cother 2018 09:07  Correct as 1 to Correct as 1 to Cother 2018 09:07				
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Estandard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But to the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  But to the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot  Correct as at 15 October 2018 09:07				
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Estandard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  BILINSTRUCTION OF The Company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  BUS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot  Correct as at 15 October 2018 09:07	· · ·			
Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 15 October 2018 09:07				
Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 15 October 2018 09:07				
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  BUD BY MANAGEMENT OF THE TOTAL OF THE T	, ,			
Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Burden All accessories are manufacturing processes we cannot  Correct as at 15 October 2018 09:07				
Recommended Location				
Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 15 October 2018 09:07				
Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 15 October 2018 09:07				
Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  BUUSTRATION OF THE PROPERTY OF THE				
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 15 October 2018 09:07		Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
process and are not binding. of certain finishes.  R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ	the limitations of reproduction and printing	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:07 AM E&OE	

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio