

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LGXR26HB-HBB

Item Image	Wiring  The state of the state	Dimensions  Hemilton Linea Georgian CFX R26 2 Way Rocker			
			imary Range	Linea-Georgian CFX	
			sert Type	6 gang 10AX 2 Way Rocker	
ate Finish	Linea-Georgian CFX Connaught Bronze Frame/Connaught Bronze				
sert Colour	Connaught Bronze/Black				
AN13 Barcode	5017504046606				
mensions (Nominal)	Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm				
xing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips				
nimum Wall Box Depth	25mm				
vitched Poles	Single				
urrent Rating	10AX				
oltage	220/250V AC				
aximum Load	10 Amp inductive				
ains Frequency	50Hz				
Rating	IP2XD				
ontact Gap Minimum	3mm				
erminal Capacity 1	5 x 1mm2				
erminal Capacity 2	4 x 1.5mm2				
erminal Capacity 3	1 x 2.5mm2				
erminal Capacity 4	1 x 4mm2 Multi-strand				
erminal Capacity 5	1 x 6mm2				
arth Terminal Capacity 1	5 x 1mm2				
arth Terminal Capacity 2	4 x 1.5mm2				
arth Terminal Capacity 3	3 x 2.5mm2				
arth Terminal Capacity 4	1 x 4mm2 Multi-strand				
arth Terminal Capacity 5	1 x 6mm2				
roduct Class 1	Must be earthed				
mbient Operating Temperature	-5° to +40°C				
ecommended Location	Internal Use Only				
aximum Installation Altitude	2000m				
andard/Approval	BS EN 60669-1				
atents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB Linea-Georgian CFX is a UK Registered Design Certificate N				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:07 E			

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio