

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LGXR31PB-SBB

Item Image    Wiring   Dimensions   Dimensio	Linea-Georgian CFX Polished Brass Frame/Satin Brass Front 1 gang 10AX Intermediate Rocker Polished Brass/Black		
Primary Range Linea-Georgian CFX Inversible states Inversible Stat	Item Image	Wiring	Dimensions
Insert Type		2 Way Switch  2 Way Switch  2 Way Switch  1 0 2 1 1 0 2 1 1 0 2 1 1 0 2 1 1 0 2 1 1 0 2 1 1 0 1 1 1 1	LINEA GEORGIAN CFX R31 Intermediate Rocker
Elinear   Colour	Primary Range	Linea-Georgian CFX	
Reart Colour	Insert Type	1 gang 10AX Intermediate Rocker	
EAN13 Barcode	Plate Finish	Linea-Georgian CFX Polished Brass Frame/Satin Brass	
Dimensions (Nominal)  Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  Single  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp Inductive  Mains Frequency  50H2  IP Rating  IPZXD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  1 x 4mm2 Multi-strand  Earth Terminal Capacity 3  1 x 6mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity	Insert Colour	Polished Brass/Black	
Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  25mm  Single  Current Rating  10AX  Voltage  2202550 VAC  Maximum Load  10 Amp inductive  Mains Frequency  50Hz  IP Rating  1P2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  1 x 4 x 4 x 1.5mm2  Earth Terminal Capacity 3  1 x 4 x 4 x 1.5mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 1  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Ter	EAN13 Barcode	5017504812317	
Minimum Wall Box Depth	Dimensions (Nominal)	Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm	
Switched Poles   Single   Current Rating   10AX   Voltage   220/250V AC   Maximum Load   10 Amp inductive   Mains Frequency   50Hz   IP Rating   IP2XD   Contact Gap Minimum   3mm   Terminal Capacity 1   5 x 1mm2   Terminal Capacity 2   4 x 1.5mm2   Terminal Capacity 3   1 x 2.5mm2   Terminal Capacity 4   1 x 4mm2 Multi-strand   Terminal Capacity 4   1 x 4mm2 Multi-strand   Terminal Capacity 5   5 x 1mm2   Earth Terminal Capacity 1   5 x 1mm2   Earth Terminal Capacity 2   4 x 1.5mm2   Earth Terminal Capacity 3   1 x 2.5mm2   Earth Terminal Capacity 4   1 x 4mm2 Multi-strand   Earth Terminal Capacity 5   1 x 6mm2   Earth Terminal Capacity 4   1 x 4mm2 Multi-strand   Earth Terminal Capacity 5   1 x 6mm2   Earth Terminal Capacity 5   1 x 6mm2   Earth Terminal Capacity 4   1 x 4mm2 Multi-strand   Earth Terminal Capacity 5   1 x 6mm2   Earth Terminal Capacity 6   1 x 6mm2   Earth Terminal Capacity 9   1 x 6m	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 2 1x 2.5mm2 Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 3 1x 2.5mm2 Earth Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature .5* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.	Minimum Wall Box Depth	25mm	
Voltage	Switched Poles	Single	
Maximum Load  10 Amp inductive  SoHz  IP Rating  IPZXD  Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1 mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  1 x 4mm2 Multi-strand  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Earth Terminal Capacity 5  In Kemm2  Earth Terminal Capacity 6  In Kemm2  Product Class 1  Ambient Operating Temperature  5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. R2 2883375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R2 1 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Freefore, we reserve the right to alter designs  Freefore, we reserve the right to alter designs	Current Rating	10AX	
Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  7-5" to 440"C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to later designs	Voltage	220/250V AC	
IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5x 1mm2  Terminal Capacity 2 4x 1.5mm2  Terminal Capacity 3 1x 2.5mm2  Terminal Capacity 4 1x 4mm2 Multi-strand  Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 2 4x 1.5mm2  Earth Terminal Capacity 2 4x 1.5mm2  Earth Terminal Capacity 3 3x 2.5mm2  Earth Terminal Capacity 4 1x 4mm2 Multi-strand  Earth Terminal Capacity 4 1x 4mm2 Multi-strand  Earth Terminal Capacity 5 1x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 6069-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured an ascerdided BS EN ISO 9001 : 2015 Quality Management System.  Terminal Capacity 3 1x 6mm2  Terminal Capacity 4 1x 4mm2 Multi-strand  Terminal Capacity 5 1x 6mm2  Terminal Capacity 5 1x 6mm2  Terminal Capacity 6 1x 6mm2  Terminal Capacity 6 1x 6mm2  Terminal Capacity 7 1x 6mm2  Terminal Capacity 8 1x 6mm2  Terminal Capacity 9 1x 6mm2  T	Maximum Load	10 Amp inductive	
Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 3  1 x 4 x 1.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  To Multi-strand  Earth Terminal Capacity 5  To Multi-strand  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth	Mains Frequency	50Hz	
Terminal Capacity 2	IP Rating	IP2XD	
Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 1  Terminal Capacity 1  Terminal Capacity 2  Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 6  Terminal Capacity 7  Terminal Capacity 6  Terminal	Contact Gap Minimum	3mm	
Terminal Capacity 3  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  5° to +40°C  Recommended Location  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs		5 x 1mm2	
Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  To sem 2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Description of the Capacity of the Company to Improve products as part of our development programme.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs	Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  In 6 mm2  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs Therefore, we reserve the right to alter designs	Terminal Capacity 3	1 x 2.5mm2	
Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Terminal Capacity 4		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 6069-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs			
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BY Amm2  1 x 4mm2 Multi-strand  2 x 4 mm2 Multi-strand  2 x 4 mm2 Multi-strand  2 x 4 mm2 Multi-strand  3 x 2.5mm2  4 x 4 mm2 Multi-strand  2 x 4 mm2 Multi-strand  3 x 2.5mm2  4 x 4 mm2 Multi-strand  3 x 2.5mm2  4 x 4 mm2 Multi-s		5 x 1mm2	
Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs	Earth Terminal Capacity 2		
Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs	Earth Terminal Capacity 3		
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs	Earth Terminal Capacity 4		
Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs			
Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs	Product Class 1		
Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs		-5° to +40°C	
Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or  European standard and the product information is  correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs			
Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs			
Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Standard/Approval		
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  as part of our development programme.  Therefore, we reserve the right to alter designs	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B	
	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:07 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio