

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LGXR322PB-SBB

| Linea-Georgian CFX Polished Brass Frame/Satin Brass Front 2 gang 20AX Intermediate Rocker Polished Brass/Black                                  |                                                                                                                                                                                                       |                                                                                                                                                                                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item Image                                                                                                                                      | Wiring                                                                                                                                                                                                | Dimensions                                                                                                                                                                             |
|                                                                                                                                                 | 2 Way Switch Switch L10L2 L2 L2 L2 L2 Live Intermediate switching                                                                                                                                     | LINEA GEORGIAN CFX R322 Intermediate Rocker                                                                                                                                            |
| Primary Range                                                                                                                                   | Linea-Georgian CFX                                                                                                                                                                                    |                                                                                                                                                                                        |
| Insert Type                                                                                                                                     | 2 gang 20AX Intermediate Rocker                                                                                                                                                                       |                                                                                                                                                                                        |
| Plate Finish                                                                                                                                    | Linea-Georgian CFX Polished Brass Frame/Satin Brass                                                                                                                                                   |                                                                                                                                                                                        |
| Insert Colour                                                                                                                                   | Polished Brass/Black                                                                                                                                                                                  |                                                                                                                                                                                        |
| EAN13 Barcode                                                                                                                                   | 5017504812355                                                                                                                                                                                         |                                                                                                                                                                                        |
| Dimensions (Nominal)                                                                                                                            | Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm                                                                                                                                                  |                                                                                                                                                                                        |
| Fixing Hole Centres                                                                                                                             | Box Fixing = 60.3mm Grid Fixing = CFX Clips                                                                                                                                                           |                                                                                                                                                                                        |
| Minimum Wall Box Depth                                                                                                                          | 35mm                                                                                                                                                                                                  |                                                                                                                                                                                        |
| Switched Poles                                                                                                                                  | Single                                                                                                                                                                                                |                                                                                                                                                                                        |
| Current Rating                                                                                                                                  | 20AX                                                                                                                                                                                                  |                                                                                                                                                                                        |
| Voltage                                                                                                                                         | 220/250V AC                                                                                                                                                                                           |                                                                                                                                                                                        |
| Maximum Load                                                                                                                                    | 20 Amp inductive                                                                                                                                                                                      |                                                                                                                                                                                        |
| Mains Frequency                                                                                                                                 | 50Hz                                                                                                                                                                                                  |                                                                                                                                                                                        |
| IP Rating                                                                                                                                       | IP2XD                                                                                                                                                                                                 |                                                                                                                                                                                        |
| Contact Gap Minimum                                                                                                                             | 3mm                                                                                                                                                                                                   |                                                                                                                                                                                        |
| Terminal Capacity 1                                                                                                                             | 5 x 1mm2                                                                                                                                                                                              |                                                                                                                                                                                        |
| Terminal Capacity 2                                                                                                                             | 4 x 1.5mm2                                                                                                                                                                                            |                                                                                                                                                                                        |
| Terminal Capacity 3                                                                                                                             | 2 x 2.5mm2                                                                                                                                                                                            |                                                                                                                                                                                        |
| Terminal Capacity 4                                                                                                                             | 2 x 4mm2 Multi-strand                                                                                                                                                                                 |                                                                                                                                                                                        |
| Terminal Capacity 5                                                                                                                             | 1 x 6mm2                                                                                                                                                                                              |                                                                                                                                                                                        |
| Earth Terminal Capacity 1                                                                                                                       | 6 x 1mm2                                                                                                                                                                                              |                                                                                                                                                                                        |
| Earth Terminal Capacity 2                                                                                                                       | 5 x 1.5mm2                                                                                                                                                                                            |                                                                                                                                                                                        |
| Earth Terminal Capacity 3                                                                                                                       | 3 x 2.5mm2                                                                                                                                                                                            |                                                                                                                                                                                        |
| Earth Terminal Capacity 4                                                                                                                       | 2 x 4mm2 Multi-strand                                                                                                                                                                                 |                                                                                                                                                                                        |
| Earth Terminal Capacity 5                                                                                                                       | 1 x 6mm2                                                                                                                                                                                              |                                                                                                                                                                                        |
| Product Class 1                                                                                                                                 | Must be earthed                                                                                                                                                                                       |                                                                                                                                                                                        |
| Ambient Operating Temperature                                                                                                                   | -5° to +40°C                                                                                                                                                                                          |                                                                                                                                                                                        |
| Recommended Location                                                                                                                            | Internal Use Only                                                                                                                                                                                     |                                                                                                                                                                                        |
| Maximum Installation Altitude                                                                                                                   | 2000m                                                                                                                                                                                                 |                                                                                                                                                                                        |
| Standard/Approval                                                                                                                               | BS EN 60669-1                                                                                                                                                                                         |                                                                                                                                                                                        |
| Patents and Trademarks                                                                                                                          | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 |                                                                                                                                                                                        |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                                                                                                 | It is the policy of the company to improve products<br>as part of our development programme.  Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.                                                                                         | Correct as at 15 October 2018 09:07 AM E&OE                                                                                                                                            |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio