Hamilton

making connections beautifully

SL

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio | | |
|--|---|--|
| | LGXSPNRB-RBB | |
| Linea-Georgian CFX Richmond Brou | nze Frame/Richmond Bronze Front 1 gang 13 | 3A Double Pole Fused Spur and Neon |
| | Richmond Bronze/Black | |
| Item Image | Wiring | Dimensions |
| | | Uzmilton |
| | Neutral Neutral | Hemilton Linea georgian CFX |
| | | SPN Switched Spur & Neon |
| | | |
| | | |
| | Live | |
| Primary Range | Linea-Georgian CFX | |
| Insert Type | 1 gang 13A Double Pole Fused Spur + Neon | |
| Plate Finish | Linea-Georgian CFX Richmond Bronze Frame/Richmond Bronze | |
| Insert Colour | Richmond Bronze/Black | |
| EAN13 Barcode | 5017504047283 | |
| Dimensions (Nominal) | Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | Double | |
| Current Rating | 13 Amp | |
| Voltage | 220/250V AC | |
| Maximum Load | 13 Amp | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 3 x 2.5mm2 | |
| Terminal Capacity 2 | 2 x 4mm2 Multi Strand | |
| Terminal Capacity 3 | 1 x 6mm2 | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 Product Close 1 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location Maximum Installation Altitude | Internal Use Only 2000m | |
| Maximum Installation Altitude Standard/Approval | 2000m BS 1363-4 | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:07 AN E&O |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville I T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered | Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84 | Listed in Strimbe LUCKINS relector DSSPUE CERT. In FM1128 |

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio