

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LGXSS2PB-PBB

Linea-Georgian CFX Polished Brass Frame/Polished Brass Front 2 gang 13A Double Pole Switched Socket Polished Brass/Black

Item Image Wiring **Dimensions** Hamilton SS2 Switched Socket Primary Range Linea-Georgian CFX Insert Type 2 gang 13A Double Pole Switched Socket Linea-Georgian CFX Polished Brass Frame/Polished Brass Plate Finish Insert Colour Polished Brass/Black EAN13 Barcode 5017504802028 Dimensions (Nominal) Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp 220/250V AC Voltage Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 1 4 x 2.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 4 1 x 10mm2 Product Class 1 Must be earthed -5° to +40°C **Ambient Operating Temperature** Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2 Additional Notes Dual Earth: Yes Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Patents and Trademarks Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme.

Therefore, we reserve the right to alter designs correct at the time of going to press. and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:08 AM process and are not binding. of certain finishes

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio