

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LGXSS2RB-RBB

Linea-Georgian CFX Richmond Bronze Frame/Richmond Bronze Front 2 gang 13A Double Pole Switched Socket Richmond
Bronze/Black

| Itam Imaga | Wiring | |
|---|---|--|
| Item Image | vviiiig | Dimensions |
| | Noutral DOUBLE POLE NO DOUBLE POLE | Hemiton LINEA GEORGIAN CFX SS2 Switched Socket |
| Primary Range | Linea-Georgian CFX | |
| Insert Type | 2 gang 13A Double Pole Switched Socket | |
| Plate Finish | Linea-Georgian CFX Richmond Bronze Frame/Richmond Bronze | |
| Insert Colour | Richmond Bronze/Black | |
| EAN13 Barcode | 5017504047481 | |
| Dimensions (Nominal) | Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | Double | |
| Current Rating | 13 Amp | |
| Voltage | 220/250V AC | |
| Maximum Load | 13 Amp | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 4 x 2.5mm2 | |
| Terminal Capacity 2 | 3 x 4mm2 | |
| Terminal Capacity 3 | 2 x 6mm2 Multi-Strand | |
| Terminal Capacity 4 | 1 x 10mm2 | |
| Earth Terminal Capacity 1 | 4 x 2.5mm2 | |
| Earth Terminal Capacity 2 | 3 x 4mm2 | |
| Earth Terminal Capacity 3 | 2 x 6mm2 Multi-strand | |
| Earth Terminal Capacity 4 | 1 x 10mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS 1363-2 | |
| Additional Notes | Dual Earth: Yes | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:08 AM E&OE |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio