Hamilton

making connections beautifully

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio | | |
|--|---|--|
| LGXT24PB-PB | | |
| | | |
| Linea-Georgian CFX Polished Brass Frame/Polished Brass Front 4 gang 20AX 2 Way Toggle Polished Brass | | |
| Item Image | Wiring | Dimensions |
| | | Hemilton Linea georgian cfx |
| | | T24 |
| | Image: specific degree Image: specif | 2 Way Toggle |
| Primary Range | Linea-Georgian CFX | |
| Insert Type | 4 gang 20AX 2 Way Toggle | |
| Plate Finish | 4 gang 20AX 2 way Toggle Linea-Georgian CFX Polished Brass Frame/Polished Brass | |
| Insert Colour | Polished Brass | |
| EAN13 Barcode | 5017504802288 | |
| | Double: Height = 95.5mm Width = 154.5mm Depth = 4.0mm | |
| Dimensions (Nominal) Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips | |
| | 35mm | |
| Minimum Wall Box Depth Switched Poles | | |
| | Single 20AX | |
| Current Rating | 20/250V AC | |
| Voltage | | |
| Maximum Load | 20 Amp inductive | |
| Mains Frequency | 50Hz IP2XD | |
| IP Rating | | |
| Contact Gap Minimum | 3mm 5 x 1mm2 | |
| Terminal Capacity 1 | | |
| Terminal Capacity 2 | 4 x 1.5mm2 | |
| Terminal Capacity 3 | 2 x 2.5mm2 | |
| Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Terminal Capacity 5 | 1 x 6mm2 | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-1 | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:08 AM E&OE |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 | | |

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio