

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LGXT31PB-PB

Primary Range Linear Type 1 guary 20XX Intermediate Togglit Float Type 1 guary 20XX Intermediate Type 2 guary 2	Linea-Georgian CFX Polished Brass Frame/Polished Brass Front 1 gang 20AX Intermediate Toggle Polished Brass		
Pérmair Range Lines-Georgian CFX Inventidates witching Inventidates I	Item Image	Wiring	Dimensions
Insert Type		2 Way Switch Switch 2 Way Switch L1 0 2 L2 L	LINEA GEORGIAN CFX T31 Intermediate Toggle
Plate Finish Insert Colour Polished Brass Insert Colour Polished Brass Parame Polished Brass Fame Polished Arm Polished Brass Fame Polished Arm Polished Brass Fame Polished Brass Fame Polished Arm Polished Brass Fame Polished Brass Fame Polished Brass Fame Polished Arm Polished Brass Fame Polished Brass Fame Polished Brass Fame Polished Brass Fame Polished Arm Polished Brass Fame Pol	Primary Range	Linea-Georgian CFX	
Polished Brass	Insert Type	1 gang 20AX Intermediate Toggle	
EAN13 Barcode 5017504802295 Dimensions (Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XID Contact Gap Minimum 3mm Terminal Capacity 1 5 x tmm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity	Plate Finish	Linea-Georgian CFX Polished Brass Frame/Polished Brass	
Dimensions (Nominal) Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm	Insert Colour	Polished Brass	
Riving Hole Centres	EAN13 Barcode	5017504802295	
Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 3 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature -5* to 440*** Recommended Location Internal Use Only Maximum Installation Altitude 200m <	Dimensions (Nominal)		
Switched Poles Single Current Rating 20XX Voltage 220/250V AC Maximum Load 29 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 2x 4.mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 6x 1.mm2 Earth Terminal Capacity 2 5x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 4 2x 4.mm2 Multi-strand Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 4 2x 4.mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60689-1 <	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Current Rating 20AX Voltage 220/250 V AC Maximum Load 20 Amy inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ms be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 200m Standard/Approval BS EN 6669-1 Linea is a Registered Trade Mark No 238665 Cris a Regi	Minimum Wall Box Depth	35mm	
Voltage 220/250V AC Maximur Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4 mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5* 10 + 40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 European standard and the product information is correct at the time of ging to press. Linea Is a Regi	Switched Poles	Single	
Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 5mm2 Earth Terminal Capacity 1 6 x 1 mm2 Earth Terminal Capacity 1 6 x 1 mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 1 x 6mm2 Froduct Cla	Current Rating		
Mains Frequency 50Hz P Rating 1P2D Contact Gap Minimum 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 6 x 1mm2 Earth Terminal Capacity 1 6 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 1 Earth Terminal Capacity 9 Earth Termina	Voltage	220/250V AC	
PRating P2XD	Maximum Load	20 Amp inductive	
Contact Gap Minimum Terminal Capacity 1 5 x 1 mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Internal Capacity 9 Inter	Mains Frequency		
Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or European standard and the product information is Correct at the time of going to press. All products listed conform to current British or European standard and the product information is Correct at the time of going to press. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not brinding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of or certain finishes. Correct as at 15 October 2018 09:08 AM EAOE	IP Rating	IP2XD	
Terminal Capacity 2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 I x 6mm2 Earth Terminal Capacity 5 I x 6mm2 Earth Terminal Capacity 5 I x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398665 European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Due to manufactured under an accredited as a part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. EXOC Tered as at 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 09:08 AM EXOC Tered as a 15 October 2018 0	Contact Gap Minimum		
Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Number No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Number No 2398665 CFX is a Numer No 2398665 CFX is a Number No 2398665 CFX is a Number No 239	Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 09:08 AM EAOE	Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 5	Terminal Capacity 3		
Earth Terminal Capacity 1	Terminal Capacity 4		
Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BEN 150 9001 : 2015 Quality Management System. Due to manufactured under an accredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 09:08 AM E&OE	Terminal Capacity 5		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.			
Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea is a Registered Trade Mark No 2398667 Patent No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All coessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All coessories are manufactured under an accredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BUILUstrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Earth Terminal Capacity 2		
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 09:08 AM E&OE			
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 09:08 AM E&OE	• • •		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. But to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.			
Recommended Location			
Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. But to the limitations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes.			
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.		·	
Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 09:08 AM E&OE			
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 09:08 AM E&OE of certain finishes.		Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B	
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of certain finishes.	European standard and the product information is	All accessories are manufactured under an accredited	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of of certain finishes.	E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio