



LGXTCMAB-SBB

Linea-Georgian CFX Antique Brass Frame/Satin Brass Front 1 gang Telephone Master Black

Item Image	Wiring	Dimensions																								
	<table border="1" data-bbox="662 468 964 600"> <thead> <tr> <th>Pin No.</th> <th>BT Wiring Schedule</th> <th>Colour Codes:</th> </tr> </thead> <tbody> <tr> <td colspan="3" style="text-align: center;">Striped Wires</td> </tr> <tr> <td>1</td> <td>GREEN / White</td> <td></td> </tr> <tr> <td>2</td> <td>BLUE / White</td> <td></td> </tr> <tr> <td>3</td> <td>ORANGE / White</td> <td></td> </tr> <tr> <td>4</td> <td>WHITE / Orange</td> <td></td> </tr> <tr> <td>5</td> <td>WHITE / Blue</td> <td></td> </tr> <tr> <td>6</td> <td>WHITE / Green</td> <td></td> </tr> </tbody> </table> <p data-bbox="672 600 954 609" style="text-align: center;">Main Wire Colour shown in CAPITALS</p> <p data-bbox="711 611 915 659" style="text-align: center;">Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.</p> <p data-bbox="662 684 974 762">The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel, ie Pin 1 to Pin 1 ; Pin 2 to Pin 2 ; etc. as shown in the diagram above.</p>	Pin No.	BT Wiring Schedule	Colour Codes:	Striped Wires			1	GREEN / White		2	BLUE / White		3	ORANGE / White		4	WHITE / Orange		5	WHITE / Blue		6	WHITE / Green		 <p data-bbox="1235 453 1398 527" style="text-align: center;">Hamilton LINEA GEORGIAN CFX TCM Telephone Master Socket</p>
Pin No.	BT Wiring Schedule	Colour Codes:																								
Striped Wires																										
1	GREEN / White																									
2	BLUE / White																									
3	ORANGE / White																									
4	WHITE / Orange																									
5	WHITE / Blue																									
6	WHITE / Green																									
Primary Range	Linea-Georgian CFX																									
Insert Type	1 gang Telephone Master																									
Plate Finish	Linea-Georgian CFX Antique Brass Frame/Satin Brass																									
Insert Colour	Black																									
EAN13 Barcode	5017504781644																									
Dimensions (Nominal)	Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm																									
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips																									
Minimum Wall Box Depth	25mm																									
Switched Poles	N/A																									
IP Rating	IP2XD																									
Contact Gap Minimum	N/A																									
Earth Terminal Capacity 1	5 x 1mm ²																									
Earth Terminal Capacity 2	4 x 1.5mm ²																									
Earth Terminal Capacity 3	3 x 2.5mm ²																									
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand																									
Earth Terminal Capacity 5	1 x 6mm ²																									
Product Class 1	Must be earthed (ref BS7671 415.2.1)																									
Ambient Operating Temperature	-5° to +40°C																									
Recommended Location	Internal Use Only																									
Maximum Installation Altitude	2000m																									
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673																									
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																								
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at 15 October 2018 09:08 AM E&OE																								

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM1238