Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio		
LGXTCMRB-RBB		
Linea-Georgian CFX Richmond Bronze Frame/Richmond Bronze Front 1 gang Telephone Master Black		
Item Image	Wiring	Dimensions
	Pin BT Wiring Schedule Colour Codes: Striped Wires 1 GREEN / White 2 BLUE / White 3 ORANGE / White 4 WHITE / Orange 5 WHITE / Blue 6 WHITE / Green Main Wire Colour shown in CAPITALS Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected. The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected to any one exchange line is 2. Any number of sockets may be connected. All sockets are connected to any one exchange line is 2. Any number of sockets may be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1 : Pin 2 to Pin 2 ; etc. as shown in the diagram above.	ELECTRICAL CONSIGNATION OF THE CONSIGNATION OF
Primary Range	Linea-Georgian CFX	
Insert Type	1 gang Telephone Master	
Plate Finish	Linea-Georgian CFX Richmond Bronze Frame/Richmond Bronze	
Insert Colour	Black	
EAN13 Barcode	5017504047818	
Dimensions (Nominal)	Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	25mm	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:08 AN E&OI
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville R T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered (E: info@hamilton-litestat.com www.hamilton-litestat.com	oad, Brislington, Bristol, BS4 5NZ Mice 1 Rushmills, Bedford Road, Northampton NN4 7YB a London No. 941624 VAT Registration No. 222 6607 84	Listed in Trimble. LUCKINS roduct selector

SL